

OPTIMAL Junior® with DÄMMGULAST®, galvanised

Application

- Suitable for pipe attachments in industrial areas
- Suitable for fastening of drinking water and heating pipes
- For indoor use

Your advantages

- Practical latching fastener
- Easy clicking-in of the fastening bolt with the tip of a finger
- High safety due to the positive-fit edge hook-in opening
- The pipe is free to move during the installation
- No inadvertent opening once it has clicked in, due to the safety latching fastener
- Quick installation due to the single fastening bolt
- The easy click-in fastener allows opening and closing of the pipe clamp with only one hand



- Captive fastening bolt
- Fastener retains the pipe securely even at the full opening angle of the clamp
- DÄMMGULAST® vibration control lining with green identification stripe: average sound level improvement up to 18 dB(A)




- Vibration control tested
- This product is awarded with the „Gütezeichen Rohrbefestigung“ (quality mark of pipe support) and is submitted to controls according to RAL-GZ 655-B

Features



Size	Max. recommended load [N]
12 mm - 1¼"	400
1½" - 2"	500
70 - 83 mm	850
3" - 4"	1,000



Connecting thread	Size		Clamping range [mm]	Dimensions [mm]					Part no.	Sales unit	Pack unit
	[inch]	[mm]		b1	B	H	H1	V			
M	M8	12	12 - 14	23	50	20	33	M5	141485	100	Pieces
		¾"	15 - 18		54	22	37		136101		
		½"	19 - 22		58	24	41		136102		
		¾"	23 - 27		63	27	46		136103		
		28	26 - 30		66	28	49		141486		
		1"	32 - 35		71	31	54		141487		
		40	37 - 41		77	33	60		141488		
		1¼"	42 - 46		82	36	65		141489		
M8/M10	2"	1½"	48 - 51	28	88	39	71	M6	141490	50	Pieces
		55	53 - 58		94	51	86		141491		
		70	59 - 64		101	54	93		141492		
		2½"	68 - 73		119	59	101		119532		
		74 - 80	126		62	108	119536				
		83	83 - 87		132	65	114		119540		
		3"	89 - 92		137	68	119		119544		
		102	100 - 104		148	73	130		119473		
110	108 - 111	156	77	138	119477						
4"	112 - 115	160	79	142	119481						