

VARIO-Twin pipe clamps

galvanised

Application


- Ideal for parallel pipes
- Ideal as support for risers or suspended pipes
- Ideal for good appearance as the safety fastener is on the inside
- Suitable for attachment of pipelines in residential and industrial constructions
- For indoor use


Your advantages

- Twin clip has the fastening advantages of the safety clip
- Safety fastener without fastening screws
- Distance between pipe axes is adjustable
- Markings faciliate the distance adjustments
- Allows combination of different pipe diameters on one twin clip



- Efficient support for 2 pipes with one anchor plug
- DÄMMGULAST® vibration control lining with green identification stripe: average sound level improvement up to 18 dB(A)





Features



Suitable for	Size	Adjustment range	Dimensions [mm]			Part no.	Sales unit	Pack unit
	[mm]	A [mm]	В	Н	H1			
Copper pipes	12	40 - 80	23 + A	22	32	107300	50	Pieces
	15		28 + A	24	35	107301		
	18		31 + A	25	38	107302		
	20			26	40	107303		
	22		35 + A	27	42	107304		
	24		37 + A	28	44	107305		
	28	50 - 95	42 + A	30	48	107306		
	30		46 + A	31	50	107309		
	33			33	53	107310		
	35			34	55	107311		
	42	60 - 105	56 + A	37	62	107312		



The mounting distance of the pipe from the structure element is determined by the selection of the appropriate bolt screw length. The distance can be adjusted by means of the nut and locknut. The fitting of the VARIO-Twin bracket by means of anchors enables the distance from the structure to be continuously adjusted while maintaining flexural rigidity.