

Pipe loops type EHS

galvanised

Application

- For fastening sprinkler pipes as per VdS and FM Guidelines

Your advantages


- One-piece design allows quick and easy installation of sprinkler pipes
- Approved by VdS and FM
- Ideal for suspension using threaded pins and threaded rods
- Easy height adjustment on a threaded rod or threaded pin



Features



Size	Max. recommended load [N]
1" - 2"	2,000
2½" - 4"	3,500
5" - 6"	5,000
8"	8,500
10"	11,000



Connecting thread M	Size	Pipe outer Ø D [mm]	VdS *	FM	b	Dimensions [mm]			Part no.	Sales unit	Pack unit	
						s	H	H1				
M8	1"	33.7	x		12	1.5	55	83	170636	100	Pieces	
	1¼"	42.4	x					88	170637			
	1½"	48.3	x				60	96	170638			
	2"	60.3	x				69	110	170639			
M10	1"	33.7	x	x	15	2.5	55	86	170640	100		
	1¼"	42.4	x	x				90	170641			
	1½"	48.3	x	x			60	96	170642			50
	2"	60.3	x	x			69	113	170643			
	2½"	76.1	x	x			85	138	170644	25		
	3"	88.9	x	x			100	160	170645			
	4"	114.3	x	x			130	202	170646			
M12	5"	139.7	x	x			145	232	170647	20		
	6"	168.3	x	x			173	275	170648			
M16	8"	219.1	x	x	25		220	352	170649	10		
M20	10"	273	x		20	3	307	470	153221	15		

* Article 153221 with VdS approval G 413023