MÜPRO

DÄMMGULAST® red

Application

- Ideal pipe clamp lining for high temperature range up to 200 °C

Your advantages

- Average vibration reduction up to 24 dB(A) due to 6 mm cylindrical profile
- Resistant to temperatures up to 200 °C
- Temperature range from -60 °C to +200 °C
- Prevents the occurrence of friction and stiction noises caused by thermal, axial expansion of the pipe
- Prevents the build-up of forces on the attachment due to the good rolling motion of the lining
- Clip-over edges prevent the lining from slipping out of the clamp



Features

Size	Design	Length [m]	Dimensions [mm] A	B	C	Part no.	Sales unit	Pack unit
20 x 6 mm	3-string	30	6	3	20	**108002**	1	Roll
25 x 6 mm	4-string			4	25	**108003**		
30 x 6 mm					30	**108005**		
40 x 6 mm	6-string			6	40	**108006**		
50 x 6 mm	7-string			10	50	**108008**		

DÄMMGULAST® seawater proof

Application

- Seawater resistant material, specially suitable for shipbuilding and off-shore applications

Your advantages

- Average vibration reduction up to 20 dB(A) due to 6 mm cylindrical profile
- Prevents the occurrence of friction and stiction noises caused by thermal, axial expansion of the pipe
- Prevents the build-up of forces on the attachment due to the good rolling motion of the lining
- Clip-over edges prevent the lining from slipping out of the clamp
- Silicone-free
- Vibration control tested



Features

Size	Design	Length [m]	Dimensions [mm] A	B	C	Part no.	Sales unit	Pack unit
20 x 6 mm	2-string	30	6	3	20	**108217**	1	Roll
30 x 6 mm	3-string			4	30	**108219**		
40 x 6 mm	5-string			6	40	**108220**		
50 x 6 mm	6-string			8	50	**108221**		
60 x 6 mm	7-string			10	60	**108222**		

⚠ In order to accommodate large changes of pipe lengths, pipe guides allowing axial motion should be provided at the fixing points (see chapter „Anchor/expansion points„). Vibration control linings are generally not suitable for vibration control at the pipe anchor point. For taking up the anchor point forces and providing good vibration control, PHONOLYT® Anchor point for pipes should be used.

© MÜPRO