

MPR-Threaded plates

galvanised

Application

- For fixing of attachment parts in the rail slot of the MPR-Support channels
- For indoor use


Your advantages

- Interlocking threaded plate for secure positive connection in the rail slot of the MPR-Support channels
- Galvanised version for use in dry interiors



Features

Material thickness of support channel [mm]	Connecting thread	Max. recommended tensile load F _z [N]	Tightening torque [Nm]
		with threaded pin 4.6 and washer 40 x 3 mm	
1.5	M8	3,100	9
	M10		17
	M12		29
2.0	M6	2,400	4
	M8	4,500	9
	M10		17
	M12		29
	M16		
2.5	M6	2,400	4
	M8	4,500	9
	M10	5,000	17
	M12		29
	M16		



For profiles	Thread	Dimensions [mm]			Part no.	Sales unit	Pack unit
		B	L	s			
41/21/2.0, 41/41/2.0, 41/41/2.5, 41/62/2.5, 41/42/2.0, 41/82/2.0, 41/124/2.5	M6	19.5	34.5	6	151051	100	Pieces
41/21/1.5, 41/21/2.0, 41/41/2.0, 41/41/2.5, 41/62/2.5, 41/42/2.0, 41/82/2.0, 41/124/2.5	M8			8	151052		
41/21/1.5, 41/21/2.0, 41/41/2.0, 41/41/2.5, 41/62/2.5, 41/82/2.0, 41/124/2.5	M10			9	151053		
	M12				151054		
41/41/2.0, 41/41/2.5, 41/62/2.5, 41/82/2.0, 41/124/2.5	M16	30.5		10	151055	25	