


Hanger sockets with inner thread and reinforcement ring

with round hole, galvanised

Thread	Hole diameter [mm]	Max. recommended tensile load [N]	Dimensions [mm]					Part no.	Sales unit	Pack unit
			C	D	L	L1	b			
M8	8.5	3,600	14	8.5	50	29	25	106600	100	Pieces
M10	10.5	4,600	15	10.5	52	30	30	106597		
M12	13	3,600		13				106598		



Hanger sockets with inner thread and reinforcement ring 45°

with round hole, galvanised


Thread	Hole diameter [mm]	Max. recommended tensile load [N]	Dimensions [mm]					Part no.	Sales unit	Pack unit
			C	D	L	L1	b			
M8	8.5	1,700	14	8.5	50	29	25	174423	100	Pieces
M10	10.5	2,700	15	10.5	52	30	30	174424		
M12	13	1,700		13				174450		



Slot bolt

with metric thread, galvanised

Thread	Oblong hole V	Dimensions [mm]			Part no.	Sales unit	Pack unit
		A	L	L1			
M8	8.5 x 25 mm	28	77	30	114454	100	Pieces



Eye bolts with metric thread

forged, galvanised

Thread	Total length [mm]	Thread length [mm]	Hole diameter [mm]	Outer diameter eye bolt [mm]	Part no.	Sales unit	Pack unit
M8	52	20	8.5	21	120053	100	Pieces
M10	61	22	10.5	24	120041		



Base plates with hexagonal nut

galvanised

Size	Thread	Oblong hole V	Hole-centre distance C [mm]	Dimensions [mm]			Part no.	Sales unit	Pack unit
				L	b	s			
1	M8	9 x 16 mm	54	80	30	3	112407	10	Pieces
	M10						112395		
	M12						112401		
2	M8	11 x 19 mm	80	120	40	4	112467		
	M10						112451		
	M12						112459		
	M16						112463		

