Turnbuckles

DIN 1480, hot-dip galvanised

Thread	Length [mm]	Adjustment range [mm]	Max. recommended tensile load [N]	Part no.	Sales unit	Pack unit
M12	125	80	9,300	**125010**	1	Pieces
M16	170	110	17,700	**125016**		

Washers

DIN 125, hot-dip galvanised

For thread	Outer diameter [mm]	Inner diameter [mm]	Thickness [mm]	Part no.	Sales unit	Pack unit
M8	16	8.4	1.6	**127346**	1	Pieces
M10	20	10.5	2	**127318**	100	
M12	24	13	2.5	**127325**		
M16	30	17	3	**127328**		



Washers

for MPC-Support channels, hot-dip galvanised

For thread	Outer diameter [mm]	Inner diameter [mm]	Thickness [mm]	Part no.	Sales unit	Pack unit
M8	24	8.4	2	**162200**	1	Pieces
M10	30	10.5	2.5	**132832**		



Washers

for MPR-Support channels, mechanically galvanised

For thread	Outer diameter [mm]	Inner diameter [mm]	Thickness [mm]	Part no.	Sales unit	Pack unit
M8	40	8.4	3	**154239**	100	Pieces
M10		10.5		**154240**		
M12		13		**154241**		
M16		17		**154242**	50	



Link chain

DIN 763, hot-dip galvanised

Size	Length [m]	Part no.	Sales unit	Pack unit
4 x 32 mm	30	**112096**	1	Roll

06/2026

© MÜPRO