

Punched tapes


galvanised or plastic coated

Application

■ Efficient punched tape for simple fastening jobs

Your advantages

- Easy to handle due to versatile mounting accessories
- Can be fitted with DÄMMGULAST® Junior vibration control lining







Features

Design	Width b [mm]	Max. recommended load [N]
straight edges, galvanised corrugated edges, galvanised	17 12	740 480
	17	800
plastic coated	19	1,100
	27	1,300

Design	Width b [mm]	For thread	Hole diameter D [mm]	Hole-centre distance C [mm]	Length [m]	Part no.	Sales unit	Pack unit
straight edges, galvanised	17	M6	6.5	12	10 50	114798 114804	20 1	Roll
corrugated edges, galvanised	12 17	M5 M6	5.5 6.5	14.5 20	10	114807 114801		
plastic coated	19 27	M8	8.5	15		114786 114789		



Rolls of 50 m are supplied in a practical dispenser case.

Bolts with nuts for punched tapes, galvanised

Connecting thread	Screw length [mm]	Part no.	Sales unit	Pack unit
M8	25	121167	100	Pieces



Washers for punched tapes, galvanised

For thread	Outer diameter [mm]	Inner diameter [mm]	Thickness [mm]	Part no.	Sales unit	Pack unit
M6	12	6.4	1.6	127307	100	Pieces
M8	16	8.4		127310		

