

Pipe connectors DUPLO

Chrome steel

Application

- For connecting cast iron (SML) pipes and fittings according to DIN 19522/ EN 877

Your advantages

- Pipe connector with two screws
- Compact design enables fitting in confined spaces
- Wide tightening strap guarantees extensive distribution of the clamping force
- Tightening strap made of high quality chrome steel

- Creased, dimensionally stable transition lip ensures uniform contact of the sealing collar on the pipe, even in the sealing region
- Simple fitting due to combihead bolt with hexagonal longitudinal slot
- Uniform clamping force distribution due to stable seal with large area pressure-plate
- Tightening bolts integrated into the pressure plate, no loose nuts
- Tested and approved by the Material Testing Institute of North Rhine-Westphalia, supervision contract Nr. 117430



Type DN 50-DN 150, one-piece



Type DN 200-DN 300, two-piece

Features



Design	Nominal size DN	Pipe outer Ø [mm]	Thread	Allen bolt spanner width [mm]	Part no.	Sales unit	Pack unit
one-piece	50	58	M8	10	115214	50	Pieces
	70	78			115217		
	80	83			130659	40	
	100	110			115176	50	
	125	135			115182	25	
	150	160			115188	10	
two-piece	200	210	115194	5			
	250	274	115200	4			
	300	326	115205	1			