

# Pipe connectors MONO

Chrome steel

## Application

- For connecting cast iron (SML) pipes and fittings according to DIN 19522/EN 877

## Your advantages

- Simple visual check at the control slot if required tightening torque has been reached
- No torque spanner necessary
- The optimum tightening torque can be achieved despite variations in pipe size (within the tolerance)
- The single-bolt pipe connector is easy to fit and easy to handle
- The tightening bolt with hexagonal socket head enables fast fitting to and removal from the pipe
- Tightening strap made of high quality chrome steel
- Uniform tightening due to the wide central fastening
- A double seam at the sealing collar guarantees a strong radial contact with the pipe and allows the quick pre-assembly of pipes and plain fittings
- The strong fastening has a large adjustment range and thus compensates variations in pipe diameter
- The generously dimensioned inlet sealing lip allows easy insertion of the pipe or fitting
- Sealing collar in high-quality, boiling water resistant elastomeric material
- Tested and approved by the Material Testing Institute of North Rhine-Westphalia, supervision contract Nr. 117430



Before tightening the pipe connector: control slot open



Visual check: After tightening the pipe connector: control slot closed



## Features



Design	Nominal size DN	Pipe outer Ø [mm]	Thread	Allen bolt spanner width [mm]	Part no.	Sales unit	Pack unit
one-piece	50	58	M8	6	115244	50	Pieces
	80	83			115262		
	100	110			115223		
	125	135			115229	25	
	150	160			115235	20	
	200	210	M10	8	144583	5	



The function of the MÜPRO control slot is a registered design.  
Pipe connector DN 200 without control slot.