MÜPRO

Plasterboard plugs

Design	Screw diameter	Part no.	Sales unit	Pack unit
Metal	Chipboard screws 4 - 4.5	**179490**	100	Pieces
Plastic	Drywall screws 3.6 - 4.2 Chipboard screws 3.5 - 6 Wood screws 3.5 - 5	**179491**	200	

The plasterboard plug can be mounted without pre-drilling.

Non-load-bearing masonry, plaster or insulation must be taken into account. These are not considered as anchoring grounds.

Nail plugs

Application

- Suitable for attachment in concrete, lime sand brick, solid brick

Your advantages

- Long spread zone for optimum grip
- Robust design of nail screw and plug withstands high impact forces
- Countersunk design of nail allows surface-flush installation
- Delivery pre-assembled prevents nail loss

Features

Plug diameter [mm]	Anchor length [mm]	Drilling depth [mm]	Anchoring depth [mm]	Max. recommended load			Part no.	Sales unit	Pack unit
				Concrete B25 [N]	Solid brick [N]	Lime sand brick [N]			
6	35	35	25	300	270	230	**179483**	200	Pieces
	50						**179484**		
	60						**179485**		
	80						**179486**		
8		45	40	420	390	340	**179487**	100	
	100						**179488**		
	120						**179489**		

DE

Non-load-bearing masonry, plaster or insulation must be taken into account. These are not considered as anchoring grounds.