

Laminated plastic signs

Application

■ High quality laminated plastic signs for marking of pipelines, fittings etc. meeting the high resistance requirements of the sign

Your advantages


- Wide range of background colours available for the sign
- Standard sign size 100 x 50 mm suitable for the mounting base with protective cover
- Fire performance corresponds to fire class B2 (DIN 4102)
- Applicable outdoors
- Water resistant
- High resistance to chemicals
- Light-fast
- High-quality surface finish (approx. 500 N/mm² micro Vickers hardness)
- High gloss
- Printed according to individually styled specifications
- With engraved text according to customer specifications
- Also available with self-adhesive reverse side or with drilled holes



Terms and texts, engraved: Individual terms and texts can be engraved on the laminated plastic signs according to customer requirements



Alternatively with full print: Text according to customer specification in combination with individual logo in company's colours is imprinted on the laminated-plastic sign with a robust carrier foil



Printing of signs

Features

Temperature range	long-term: -40 °C to + 80°C, short-term: up to +180 °C
Standard text height	7 mm (20 characters per line, maximum, and 4 lines, maximum)

Design	Colour of the sign	Colour of the engraving	Number of print colours [pieces]	Number of engraved lines [pieces]	Part no.	Sales unit	Pack unit
Laminated plastic sign	white	black	-	-	119361	100	Pieces
	red	white			119377		
	green				119373		
	blue				119369		
	yellow	black			119353		
	grey				119357		
	black	white			119381		
Printing of rows of text (Print area 2)		-			107355	1	
Digitisation of design specified by customer (to be ordered one-time only, with first order)					132267		
Engraving of lines of writing				1	112841		
				2	112843		
				3	112845		
				4	112847		
Printing, with company logo 100 x 14 mm (Print area 1)			1	-	139995		
			2		139997		
			3		139998		
			4		139999		

