

Cutting-off discs

Application

- For machining various materials
- Can be used on building site as well as in the factory

Your advantages

- Long lifetime

- High resistance to fracture and side loading
- Low heating up of the material
- High cutting performance
- Max. peripheral speed 80 m/sec
- Manufactured according to EN 12413



Outer diameter [mm]	Inner diameter [mm]	Thickness [mm]	Design	Suitable for	Part no.	Sales unit	Pack unit
125	22	1	straight	Metal: Formed steel, cast iron, pipes, steel sheet	130220	25	Pieces

Recipro-saw blade HSS

bi-metal, for sheet metal, sectional steel and non-ferrous metals up to 8 mm thickness

Type	Suitable for	Teeth/inch [pieces]	Length [mm]	Part no.	Sales unit	Pack unit
P-04911	Steel and non-ferrous metals from 3 to 8 mm	14	150	113416	5	Pieces
P-04927			200	113419		



Work gloves

MAXIFLEX Ultimate, breathable and silicone-free

Size	Part no.	Sales unit	Pack unit
8	160455	1	Pair
10	151740		



Garbage bags

volume approx. 120 litres

Thickness [µm]	Content [pieces/roll]	Part no.	Sales unit	Pack unit
45	25	118982	1	Pieces
75	15	167365		

