

MPC-Support channels



27/18 L (light), sendzimir galvanised

Application

- Ideal for pipe installation as support structure as well as for air ducts in dry interiors
- Variety of mounting options for pre-wall installations and shelves in combination with extensive range of system components

Your advantages

- Fast and efficient attachment of piping and pipe routes
- Scale marks sideways and on the side with the slot simplify the alignment of the attachment elements during installation and facilitate the measuring and cutting to length of the section on site
- For secure fixing that is adjustable laterally and vertically
- High bending stiffness due to the cross-section design
- For setting up structures with correctly measured static loads by means of diverse connection components
- Suitable vibration control elements for all support channels available
- Clean-cut appearance by the use of MPC-protection caps



Profile 27/18 L

Profile	Length [mm]	Part no.	Sales unit	Pack unit
27/18/1.0 L	2,000	129876	2	Pieces

MPC-Support channels








sendzimir galvanised

Application

- Ideal for pipe installation as support structure as well as for air ducts in dry interiors
- Variety of mounting options for pre-wall installations and shelves in combination with extensive range of system components

Your advantages

- Fast and efficient attachment of piping and pipe routes
- Scale marks sideways and on the side with the slot simplify the alignment of the attachment elements during installation and facilitate the measuring and cutting to length of the section on site
- For secure fixing that is adjustable laterally and vertically
- High bending stiffness due to the cross-section design
- For setting up structures with correctly measured static loads by means of diverse connection components
- Suitable vibration control elements for all support channels available
- Clean-cut appearance by the use of MPC-protection caps



Profile 27/18



Profile 28/30



Profile 38/24

Profile	Length [mm]	Part no.	Sales unit	Pack unit
27/18/1.25	1,000	129883	1	Pieces
	2,000	129911		
	3,000	105208		
	6,000	130003		
28/30/1.75	2,000	118590	5	
	3,040	118692		
	4,000	118822		
	6,000	118994		
38/24/1.75	2,000	139920	1	
	3,040	153256		
	6,000	139922		

MPC-Support channels







sendzimir galvanised

Application

- Ideal for pipe installation as support structure as well as for air ducts in dry interiors
- Variety of mounting options for pre-wall installations and shelves in combination with extensive range of system components

Your advantages

- Fast and efficient attachment of piping and pipe routes
- Scale marks sideways and on the side with the slot simplify the alignment of the attachment elements during installation and facilitate the measuring and cutting to length of the section on site
- For secure fixing that is adjustable laterally and vertically
- High bending stiffness due to the cross-section design
- For setting up structures with correctly measured static loads by means of diverse connection components
- Suitable vibration control elements for all support channels available
- Clean-cut appearance by the use of MPC-protection caps
- Support channels 38/40 and 40/60 are awarded the RAL-quality mark of the „Gütegemeinschaft Rohrbe-
festigung“



Profile 38/40



Profile 39/52



Profile 40/60

Features



Profile	Length [mm]	Part no.	Sales unit	Pack unit
38/40/2.0	2,000	129917	1	Pieces
	3,040	129945		
	4,000	129964		
	6,000	130011		
39/52/2.5		130015		
40/60/3.0	2,000	129921		
	3,040	129946		
	4,000	129965		
	6,000	130020		



For use in areas with requirements on the duration of fire resistance, the boundary conditions set out in the fire test report must be observed.

MPC-Support channels


sendzimir galvanised

Application

- Ideal for pipe installation as support structure as well as for air ducts in dry interiors
- Variety of mounting options for pre-wall installations and shelves in combination with extensive range of system components

Your advantages

- Fast and efficient attachment of piping and pipe routes
- Scale marks sideways and on the side with the slot simplify the alignment of the attachment elements during installation and facilitate the measuring and cutting to length of the section on site
- For secure fixing that is adjustable laterally and vertically
- High bending stiffness due to the cross-section design
- For setting up structures with correctly measured static loads by means of diverse connection components
- Clean-cut appearance by the use of MPC-protection caps




Profile 40/80

Features



Profile	Length [mm]	Part no.	Sales unit	Pack unit
40/80/3.0	6,000	130024	1	Pieces

 For use in areas with requirements on the duration of fire resistance, the boundary conditions set out in the fire test report must be observed.

MPC-Support channels


H-Profiles, sendzimir galvanised

Application



- Ideal for space-saving support of multisection pipeways between ceiling beams
- Ideal for pipe installation as support structure as well as for air ducts in dry interiors
- Variety of mounting options for pre-wall installations and shelves in combination with extensive range of system components

Your advantages


- Fast and efficient attachment of piping and pipe routes
- Ideal combination of high bending stiffness and ease of installation
- Channel slots on both sides allow simple and quick alignment of all suspended and floor-mounted pipe supports
- Scale marks sideways and on the side with the slot simplify the alignment of the attachment elements during installation and facilitate the measuring and cutting to length of the section on site
- Suitable vibration control elements for all support channels available
- Clean-cut appearance by the use of MPC-protection caps



Profile 38/48



Profile 38/80



Profile 40/120

Features



Profile	Length [mm]	Part no.	Sales unit	Pack unit
38/48/1.75 H	6,000	141179	1	Pieces
38/80/2.0 H	2,000	129870		
	4,000	129872		
	6,640	129874		
40/120/3.0 H		129875		



For use in areas with requirements on the duration of fire resistance, the boundary conditions set out in the fire test report must be observed.

MPC-Support channels

Technical data

Technical data of profile:

Features

Profile	Material	Surface	Admissible steel stress $\sigma_{adm.}$ [N/mm ²]	Available MPC-Rail nuts	Profile weight [kg/m]	Profile cross-section [cm ²]	Moment of inertia		Resistance moment	
							I_y [cm ⁴]	I_z [cm ⁴]	W_y [cm ³]	W_z [cm ³]
27/18/1.0 L	DX51D	sendzimir galvanised	153	M8, M10	0.5	0.56	0.2387	0.7572	0.254	0.56
27/18/1.25					0.6	0.69	0.2911	0.9554	0.31	0.707
28/30/1.75					1.15	1.36	1.3999	2.0551	0.911	1.467
38/24/1.75				M8, M10, M12, M16	1.21	1.4	1.0871	3.6213	0.905	1.905
38/40/2.0					1.82	2.21	4.3286	6.1	2.164	3.21
39/52/2.5					2.8	3.35	10.4472	9.7614	4.018	5.005
40/60/3.0					3.5	4.44	17.5426	13.3946	5.847	6.697
40/80/3.0					4.68	5.64	37.939	17.5106	9.484	8.755
38/48/1.75 H					2.43	2.79	6.1952	7.2427	2.581	3.811
38/80/2.0 H					3.58	4.42	26.3479	12.2001	6.586	6.421
40/120/3.0 H					7	8.88	115.0004	26.789	19.166	13.394

Load bearing capacities of profiles for bending around the y-axis [N]:

Profile	L [m]						L [m]					
	0.5	1.0	1.5	2.0	4.0	6.0	0.5	1.0	1.5	2.0	4.0	6.0
27/18/1.0 L	308	117	49	24	-	-	230	69	29	14	-	-
27/18/1.25	376	143	60	29	-	-	280	84	35	17	-	-
28/30/1.75	1,099	549	303	162	-	-	814	410	178	95	-	-
38/24/1.75	1,094	541	233	122	-	-	812	317	136	72	-	-
38/40/2.0	2,609	1,308	867	523	92	-	1,927	979	559	307	54	-
39/52/2.5	4,830	2,430	1,612	1,198	260	43	3,555	1,816	1,206	752	153	25
40/60/3.0	7,019	3,537	2,349	1,748	467	117	5,157	2,643	1,758	1,272	274	69
40/80/3.0	11,311	5,733	3,815	2,844	1,080	359	8,246	4,274	2,852	2,128	634	211
38/48/1.75 H	3,100	1,559	1,032	753	139	-	2,280	1,165	772	442	82	-
38/80/2.0 H	7,834	3,977	2,646	1,971	741	235	5,696	2,962	1,977	1,475	435	138
40/120/3.0 H	22,447	11,542	7,711	5,765	2,785	1,353	16,040	8,554	5,749	4,307	2,026	794
27/18/1.0 L	154	49	21	10	-	-	128	39	16	-	-	-
27/18/1.25	187	60	25	12	-	-	156	47	20	-	-	-
28/30/1.75	544	274	128	68	-	-	451	228	100	54	-	-
38/24/1.75	542	228	98	52	-	-	450	179	77	41	-	-
38/40/2.0	1,287	652	401	220	39	-	1,067	542	315	173	30	-
39/52/2.5	2,374	1,210	804	540	110	18	1,965	1,006	670	424	86	14
40/60/3.0	3,444	1,760	1,172	873	197	49	2,848	1,464	976	717	154	39
40/80/3.0	5,508	2,847	1,901	1,420	455	151	4,541	2,365	1,582	1,182	357	119
38/48/1.75 H	1,523	776	515	317	59	-	1,260	645	429	249	46	-
38/80/2.0 H	3,804	1,973	1,318	984	312	99	3,133	1,639	1,097	819	245	78
40/120/3.0 H	10,711	5,697	3,833	2,873	1,391	570	8,763	4,723	3,186	2,391	1,141	447

The determined loads apply for static loads. Calculation based on Eurocode (EC3).

The safety coefficient $\gamma = 1.54$ takes into account the partial and combination coefficients as well as the safety factor of the material.

For the given values, the permissible steel stress and the maximum permissible deflection $L/200$ are not exceeded, taking the deadweight into consideration.

MPC-Support channels

Technical data

Permissible buckling loads for profiles [N]:

Buckling length Lk [mm]	27/18/1.0 L	27/18/1.25	28/30/1.75	38/24/1.75	38/40/2.0	39/52/2.5	40/60/3.0	40/80/3.0	38/48/1.75 H	38/80/2.0 H	40/120/3.0 H
200	8,126	10,105	20,698	20,992	33,744	51,172	67,749	86,061	42,610	67,488	135,498
300	7,570	9,403	19,911	20,046	33,405	51,172	67,749	86,061	42,392	67,488	135,498
400	6,899	8,553	19,069	19,000	32,478	50,269	66,660	84,785	41,299	66,644	134,144
500	6,093	7,531	18,133	17,798	31,508	49,109	65,155	82,904	40,166	65,642	132,242
600	5,208	6,416	17,068	16,404	30,469	47,902	63,593	80,954	38,964	64,571	130,223
700	4,358	5,355	15,861	14,839	29,338	46,627	61,946	78,904	37,669	63,403	128,040
800	3,624	4,444	14,529	13,190	28,095	45,264	60,190	76,721	36,258	62,104	125,636
900	3,025	3,705	13,132	11,582	26,730	43,794	58,302	74,378	34,714	60,639	122,951
1,000	2,546	3,116	11,749	10,109	25,245	42,206	56,263	71,852	33,033	58,966	119,914
1,100	2,164	2,648	10,451	8,818	23,663	40,491	54,064	69,128	31,226	57,046	116,455
1,200	1,859	2,273	9,278	7,713	22,023	38,654	51,706	66,208	29,323	54,851	112,513
1,300	1,611	1,970	8,243	6,778	20,374	36,712	49,209	63,109	27,368	52,374	108,052
1,400	1,409	1,722	7,343	5,987	18,765	34,696	46,605	59,869	25,417	49,641	103,084
1,500	1,241	1,517	6,565	5,318	17,237	32,643	43,942	56,545	23,518	46,719	97,686
1,600	1,102	1,346	5,893	4,750	15,813	30,597	41,274	53,199	21,712	43,703	91,997
1,700	984	1,203	5,312	4,265	14,506	28,599	38,652	49,897	20,023	40,692	86,189
1,800	884	1,080	4,809	3,848	13,317	26,680	36,121	46,695	18,463	37,772	80,436
1,900	799	976	4,370	3,488	12,244	24,864	33,712	43,636	17,037	35,004	74,879
2,000	725	886	3,987	3,176	11,278	23,163	31,448	40,748	15,740	32,423	69,614
2,100	-	807	3,651	2,902	10,409	21,584	29,336	38,047	14,563	30,042	64,696
2,200		739	3,355	2,663	9,628	20,126	27,380	35,539	13,499	27,862	60,148
2,300		679	3,092	2,451	8,925	18,784	25,576	33,219	12,536	25,874	55,968
2,400		626	2,859	2,263	8,292	17,553	23,916	31,082	11,664	24,065	52,141
2,500		579	2,651	2,096	7,720	16,425	22,392	29,115	10,874	22,421	48,645
2,600		537	2,464	1,947	7,203	15,391	20,993	27,308	10,157	20,927	45,454
2,700		499	2,297	1,813	6,735	14,443	19,709	25,647	9,506	19,567	42,540
2,800		465	2,145	1,692	6,309	13,574	18,530	24,121	8,912	18,328	39,879
2,900		435	2,008	1,583	5,921	12,776	17,447	22,718	8,371	17,198	37,446
3,000		407	1,884	1,484	5,567	12,043	16,451	21,425	7,875	16,165	35,217
3,100		382	1,771	1,394	5,243	11,368	15,533	20,234	7,422	15,219	33,174
3,200		359	1,667	1,312	4,946	10,746	14,686	19,135	7,005	14,351	31,297
3,300		339	1,573	1,237	4,674	10,172	13,904	18,120	6,622	13,553	29,569
3,400		320	1,486	1,168	4,422	9,641	13,181	17,180	6,269	12,819	27,977
3,500		302	1,406	1,105	4,191	9,149	12,511	16,309	5,943	12,142	26,507
3,600		286	1,332	1,047	3,977	8,693	11,890	15,501	5,641	11,516	25,148
3,700		271	1,264	993	3,778	8,270	11,312	14,750	5,362	10,936	23,888
3,800		257	1,202	943	3,594	7,876	10,775	14,051	5,102	10,398	22,719
3,900		245	1,143	897	3,423	7,509	10,274	13,399	4,861	9,899	21,632
4,000		233	1,089	854	3,264	7,167	9,807	12,791	4,636	9,434	20,621
4,100		222	1,038	815	3,116	6,847	9,370	12,222	4,426	9,001	19,678
4,200		212	991	777	2,977	6,548	8,962	11,690	4,230	8,597	18,797
4,300		202	948	743	2,847	6,268	8,579	11,192	4,047	8,219	17,974
4,400		193	906	710	2,726	6,005	8,220	10,724	3,875	7,865	17,203
4,500		185	868	680	2,612	5,758	7,883	10,285	3,714	7,534	16,480
4,600		177	832	652	2,505	5,526	7,565	9,872	3,563	7,223	15,801
4,700		170	798	625	2,405	5,308	7,267	9,483	3,421	6,930	15,163
4,800		163	766	600	2,310	5,102	6,986	9,116	3,287	6,655	14,563
4,900		157	736	576	2,221	4,908	6,720	8,770	3,160	6,396	13,998
5,000		151	708	554	2,137	4,724	6,469	8,443	3,041	6,152	13,464
5,100		145	681	533	2,058	4,551	6,232	8,134	2,928	5,921	12,961
5,200		139	656	513	1,983	4,387	6,008	7,841	2,822	5,703	12,485
5,300		134	632	495	1,912	4,231	5,795	7,564	2,721	5,497	12,034
5,400		129	610	477	1,844	4,084	5,594	7,302	2,626	5,302	11,608
5,500		125	588	460	1,780	3,944	5,403	7,052	2,535	5,117	11,203
5,600		121	568	444	1,720	3,812	5,221	6,815	2,449	4,941	10,819
5,700		116	549	429	1,662	3,685	5,048	6,590	2,367	4,775	10,455
5,800		112	531	415	1,608	3,565	4,884	6,376	2,290	4,616	10,109
5,900		109	513	401	1,556	3,451	4,727	6,172	2,216	4,465	9,779
6,000		105	497	388	1,506	3,342	4,578	5,977	2,145	4,322	9,466



MPC-Support channels

Technical data



Buckling loads as per DIN EN 1993-1-1 sections 6.2 and 6.3.

The values in the table apply for fully bearing cross-sections and central load transmission!

The potentially lower slenderness parameter for buckling and lateral torsional buckling must be examined separately!

Buckling about the z-axis and the y-axis was considered.

The least favourable buckling load is documented in the table.

The safety coefficient $\gamma = 1.54$ takes into account the safety and combination coefficients as well as the safety factor of the material.



Determine the authoritative buckling length L_k depending on the storage conditions and the rod length l , as shown in the figure.

Read off the buckling load F as L_k from the table.

