

Declaration of performance acc. Regulation (EU) 305/2011

DoP No.: MP Vollisolierung rot DE 20130624 W1PEF304

1. Unique identification code of the product-type: W1PEF-003

2. Type or any other element allowing identification of the construction product as required pursuant to Article 11(4) :

MypoTHERM® Vollisolierung mit roter Schutzfolie
For batch or serial N° see label.

3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

Thermal insulation products for building equipment and industrial installations

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):

Müpro GmbH, Hessenstrasse 11, D-65719 Hofheim-Wallau

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex 3

7. In case of the declaration of performance concerning a construction product covered by a harmonised standard :

IBP -NB 1004- P2-220/2012, P2-221/2012, P2-234/2010, P2-282/2010, P2-345.1/2011
WFRGent NV - NB 1173 - 14818 ; 15811

9. Declared performance according to EN 14313+A1:2013

Characteristics

4.2.1 Thermal conductivity (W/m.K)

Thickness

Ø

Performances

0° C	40° C	90° C
0,036	0,040	0,053

4.2.2 Dimensions and tolerances

see label for nominal values of dimensions

see standard for tolerances

4.2.3 Dimensional stability

NPD

4.2.4 Reaction to fire

Thickness

Ø

Euroclass

4-25 mm :

12 - 42 mm

E

4.2.5 Durability characteristics

NPD

4.3.2 Maximum service temperature

ST(+) +100°C

4.3.3 Minimum service temperature

ST(-) 0°C

4.3.4 Water absorption

WS005

4.3.5 Water vapour diffusion resistance

NPD

4.3.6 Trace quantities of water soluble ions and the pH-value

CL20-F10-pH 5,5

4.3.7 Structure-borne sound transmission

NPD

4.3.8 Sound absorption

NPD

4.3.9 Release of dangerous substances

NPD


4.3.10 Continuous glowing combustion

NPD

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:



Hofheim-Wallau, 25.06.2013

i.A. Stefan Podszus,

Quality Manager