

Declaration of performance

EXCENTROFLEX COMPACT

**valid for
MypoTHERM Kompakt floor tube**

**This document is for informational use only and does not underly the actualization process.
This document can not be used for advertising or other purposes unless otherwise approved by MÜPRO in advance.
All rights reserved. Subject to change.**



DECLARATION OF PERFORMANCE

DoP No. : W1PEF400

1. Unique identification code of the product-type: W1PEF-004

2. Type or any other element allowing identification of the construction product as required pursuant to Article 11(4) :

EXZENTROFLEX® COMPACT

For batch or serial N° see label.

3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

Thermal insulation products for building equipment and industrial installations

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):

NMC sa, Gert-Noël-Straße, B-4731 Eynatten

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V: 3

7. In case of the declaration of performance concerning a construction product covered by a harmonised standard :

IBP -NB 1004- P1-369/2010, P1-073.1 /2009, P1-074.1/2009, P2-030/2011, P2-117/2010, P2-345.1/2011

FIW -NB 0751- F.2-1895/11

IBMB MPA -NB 0761- K-3514/790/11-MPA BS

9. Declared performance according to EN 14313+A1:2013

Characteristics

4.2.1 Thermal conductivity (W/m.K)

Thickness

Thickness 9 mm :

Thickness 25 to 51 mm :

Ø
diam 15 to 42 mm
diam 15 to 42 mm

Performances

0° C	40° C	90° C
0,036	0,040	0,053
0,038	0,042	0,055

4.2.2 Dimensions and tolerances

see label for nominal values of dimensions

see standard for tolerances

4.2.3 Dimensional stability

NPD

4.2.4 Reaction to fire

Thickness

9-51 mm

Ø
15-42

Euroclass
E

4.2.5 Durability characteristics

4.3.2 Maximum service temperature

4.3.3 Minimum service temperature

4.3.4 Water absorption

4.3.5 Water vapour diffusion resistance

4.3.6 Trace quantities of water soluble ions and the pH-value

4.3.7 Structure-borne sound transmission

4.3.8 Sound absorption

4.3.9 Release of dangerous substances

4.3.10 Continuous glowing combustion

NPD

ST(+) +100°C

ST(-) 0°C

WS005

NPD

CL20-F10-pH 5,5

NPD

NPD

NPD

NPD

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Name and function : X. FISCHER
Quality Manager

Eynatten, the 07.05.13