

Leistungserklärung gemäß Verordnung (EU) Nr. 305/2011

DOP- Nr. MP Bodenschlauch kompakt DE 20130624 W1PEF406

1. Unique identification code of the product-type: W1PEF-004

2. Type or any other element allowing identification of the construction product as required pursuant to Article 11(4) :

MypoTHERM® Bodenschlauch Kompakt
For batch or serial N° see label.

3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

Thermal insulation products for building equipment and industrial installations

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):

MÜPRO GmbH ; Hessenstrasse 11 ; Hofheim-Wallau

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex 3

7. In case of the declaration of performance concerning a construction product covered by a harmonised standard :

IBP -NB 1004- P1-369/2010, P1-073.1 /2009, P1-074.1/2009, P2-030/2011, P2-117/2010, P2-345.1/2011

FIW -NB 0751- F.2-1895/11

IBMB MPA -NB 0761- K-3514/790/11-MPA BS

9. Declared performance according to EN 14313+A1:2013

Characteristics

4.2.1 Thermal conductivity (W/m.K)

Thickness

9 mm

25 - 51 mm

Ø

15 - 42 mm

15 - 42 mm

Performances

0° C	40° C	90° C
0,036	0,040	0,053
0,038	0,042	0,055

4.2.2 Dimensions and tolerances

see label for nominal values of dimensions

4.2.3 Dimensional stability

4.2.4 Reaction to fire

Thickness

9-51 mm

Ø

15-42

see standard for tolerances
NPD

Euroclass
E

4.2.5 Durability characteristics

4.3.2 Maximum service temperature

4.3.3 Minimum service temperature

4.3.4 Water absorption

4.3.5 Water vapour diffusion resistance

4.3.6 Trace quantities of water soluble ions and the pH-value

4.3.7 Structure-borne sound transmission

4.3.8 Sound absorption

4.3.9 Release of dangerous substances

4.3.10 Continuous glowing combustion

NPD

ST(+) +100°C

ST(-) 0°C

WS005

NPD

CL20-F10-pH 5,5

NPD

NPD

NPD

NPD

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Unterzeichnet für den Hersteller und im Namen des Herstellers von:



Hofheim-Wallau, 25.06.2013

i.A. Stefan Podszus,
Qualitätsmanager