

European Technical Assessment ETA

valable pour

Rail d'installation MPR

Ce document est fourni à titre informatif uniquement et ne sert pas de base au processus de réalisation. Il ne peut être utilisé à des fins publicitaires ou autres sans l'accord préalable de MÜPRO.

Tous droits réservés. Sous réserve de modifications.



Evaluation Technique Européenne

ETE-25/0296 du 28/04/2025

(Version originale en langue française)

Partie Générale

Organisme d'Evaluation Technique (TAB) délivrant l'Evaluation Technique Européenne :

Centre Scientifique et Technique du Bâtiment (CSTB)

Nom commercial du produit de
construction :

Rails MÜPRO

Famille de produit à laquelle le
produit de construction appartient :

Produits pour les systèmes d'installation pour le support des
équipements techniques du bâtiment

Fabricant :

MÜPRO Services GmbH
Borsigstrasse 14
65205 Wiesbaden
Germany

Usine(s) de fabrication :

UBB Umformtechnik GmbH
Im Grund 1
91593 Burgbernheim
Germany

Cette Evaluation Technique
Européenne contient :

45 pages incluant 44 pages d'annexes qui font partie
intégrante de cette évaluation

Cette Evaluation Technique
Européenne est délivrée en
accord avec la réglementation
(EU) No 305/2011, sur la base de :

European Assessment Document (EAD)
280016-00-0602 version Juin 2020

Cette Evaluation remplace :

-

Les traductions de cette Evaluation Technique Européenne dans d'autres langues doivent correspondre pleinement au document original et doivent être identifiées comme telles. La communication de cette évaluation technique européenne, y compris la transmission par voie électronique, doit être complète. Cependant, une reproduction partielle peut être faite, avec le consentement écrit de l'organisme d'évaluation technique d'émission. Toute reproduction partielle doit être identifiée comme telle. La présente Evaluation Technique Européenne peut être retirée par l'Organisme d'Evaluation Technique émetteur, notamment sur information de la Commission conformément à l'article 25, paragraphe 3, du règlement (UE) n° 305/2011.

Partie Spécifique

1 Description Technique du Produit

Cette Evaluation Technique Européenne couvre les rails MÜPRO décrits dans les Tableaux A1 à A5. Les rails MÜPRO MPR 41/21/1.5, MPR 41/21/2.0, MPR 41/41/2.0, MPR 41/41/2.5 et MPR 41/62/2.5 sont fabriqués en acier de faible épaisseur, en forme de C. Des trous de formes circulaire ou oblongue permettent l'utilisation de fixation ou de pièces à fixer.

Les rails MÜPRO MPR 41/42/2.0 H, MPR 41/82/2.0 H, MPR 41/82/2.5 H et MPR 41/124/2.5 H se composent de deux profils de même type, reliés au niveau de l'arrière des rails de manière à assurer un ajustement de forme et une liaison résistante. Des évidements sous forme de trous oblongs et ronds permettent l'utilisation de fixations et d'attaches.

Les rails MÜPRO peuvent être coupés sur leur longueur selon les instructions du fabricant sans compromettre les performances déclarées.

Les dessins, dimensions et matériaux des rails MÜPRO sont donnés en Annexe A.

2 Définition de l'usage prévu

Les performances données dans la section 3 sont seulement valides si les rails MÜPRO répondent aux exigences des spécifications et conditions données en Annexe B.

Les essais et la méthode d'évaluation sur laquelle cette Evaluation Technique Européenne est basée mènent à supposer une durée de vie des rails MÜPRO d'au moins 50 ans à température ambiante et en atmosphère intérieure. Les indications relatives à la durée de vie ne peuvent pas être interprétées comme une garantie donnée par le fabricant, mais ne doivent être considérées que comme un moyen pour choisir le produit qui convient à la durée de vie économiquement raisonnable attendue des ouvrages.

En accord avec le Document d'Evaluation Européen EAD 280016-00-0602, le produit peut être utilisé pour :

- a) Installations pour le support des kits de sprinklers,
- b) Installations pour le support des équipements techniques du bâtiment en général,
- c) Installations pour le support des tuyaux pour le transport de gaz/carburant destinés à l'alimentation des systèmes de chauffage/refroidissement des bâtiments.
- d) Installations pour les supports visant à soutenir des tuyaux pour le transport de l'eau non destinée à la consommation humaine

3 Performances du produit et références aux méthodes utilisées pour leur évaluation

3.1 Sécurité en cas d'incendie (BWR 2)

No.	Caractéristique essentielle	Performance
1	Réaction au feu	Classe A1
2	Résistance au poinçonnement des trous au dos des rails sous exposition au feu	Performance non évaluée
3	Caractéristiques à la flexion sous exposition au feu	Performance non évaluée

3.2 Sécurité et accessibilité en cours d'utilisation (BWR 4)

No.	Caractéristique essentielle	Performance
4	Forme	Voir Annexe A
5	Dimensions	Voir Annexe A
6	Matériaux et caractéristiques de la section	Voir Annexe A et B
7	Résistance caractéristiques des trous au dos des rails à température ambiante	Performance non évaluée

4 Système d'Evaluation et de Vérification de la Constance des Performances (AVCP) appliqué, avec référence à sa base juridique

Conformément au Document d'Evaluation Européen EAD 280016-00-0602, les bases juridiques suivantes s'appliquent :

- En cas de domaine d'emploi a) prévu en Section 2 :
 Décision de la commission N° 96/577/EC telle que modifiée par la Décision 2002/592/EC de la Commission :
 Le système 1 s'applique pour l'évaluation et la vérification de la constance des performances (AVCP).
- En cas de domaine d'emploi b) prévu en Section 2 :
 Décision de la commission N° 97/161/EC de la Commission :
 Le système 2+ s'applique pour l'évaluation et la vérification de la constance des performances (AVCP).
- En cas de domaine d'emploi d) prévu en Section 2 :
 Décision de la commission N° 1999/472/EC telle que modifiée par la Décision 2001/596/EC de la Commission :
 Le système 3 s'applique pour l'évaluation et la vérification de la constance des performances (AVCP).
- En cas de domaine d'emploi c) prévu en Section 2 :
 Décision de la commission N° 1999/472/EC telle que modifiée par la Décision 2001/596/EC de la Commission :
 Le système 4 s'applique pour l'évaluation et la vérification de la constance des performances (AVCP).

5 Détails techniques nécessaires à l'implémentation du système AVCP, tel que proposé dans l'EAD concerné

Les données techniques nécessaires à la mise en œuvre du système d'Evaluation et de Vérification de la Constance des Performances (AVCP) sont définies dans le plan de contrôle (partie confidentielle de l'Evaluation Technique Européenne) déposé au Centre Scientifique et Technique du Bâtiment.



Le fabricant doit, sous la forme d'un contrat, impliquer un organisme notifié approuvé dans le domaine des systèmes de supportage pour la délivrance d'un certificat de conformité CE basé sur le plan de contrôle.

Délivrée à Marne La Vallée le 28/04/2025 par :

Loïc PAYET

Responsable de la division Structure, Maçonnerie et Partition

Tableau A1 : Dimensions et matériaux des rails MÜPRO MPR 41/21/1.5 et MPR 41/21/2.0

Illustration (Dimensions en mm et pouces)	Référence	N° de l'élément	Longueur [mm]	Matériaux et revêtements
	Rail MÜPRO MPR 41/21/1.5	175787	3 000	S250GD + Z275NA Selon la EN 10346
		175788	6 000	
	Rail MÜPRO MPR 41/21/2.0	150930	2 000	S250GD + Z275NA Selon la EN 10346
		150931	3 040	
		150932	6 000	
		154173	2 000	S235JR, galvanisé à chaud Selon la EN 10025-2
		154174	3 040	
		154175	6 000	
154393	2 000	V4A (1.4404) Selon la EN 10088-2		
154394	3 040			
154395	6 000			



Rails MÜPRO

Description du produit

Forme, dimensions, matériaux et revêtement

Annexe A1

Tableau A2 : Dimensions et matériaux des rails MÜPRO MPR 41/41/2.0 et MPR 41/41/2.5

Illustration (Dimensions en mm et pouces)	Référence	N° de l'élément	Longueur [mm]	Matériaux et revêtements	
	Rail MÜPRO MPR 41/41/2.0	150933 150934 150935	2 000 3 040 6 000	S250GD + Z275NA Selon la EN 10346	
		154176 154177 154178	2 000 3 040 6 000	S235JR, galvanisé à chaud Selon la EN 10025-2	
		154396 154397	2 000 6 000	V4A (1.4404) Selon la EN 10088-2	
		Rail MÜPRO MPR 41/41/2.5	150864 150937 150938	2 000 3 040 6 000	S250GD + Z275NA Selon la EN 10346
			154179 154180 154181	2 000 3 040 6 000	S235JR, galvanisé à chaud Selon la EN 10025-2



Rails MÜPRO

Description du produit

Forme, dimensions, matériaux et revêtement

Annexe A2

Tableau A3 : Dimensions et matériaux des rails MÜPRO MPR 41/62/2.5 et MPR 41/42/2.0 H

Illustration (Dimensions en mm et pouces)	Référence	N° de l'élément	Longueur [mm]	Matériaux et revêtements
	Rail MÜPRO MPR 41/62/2.5	150936 150978 150979	2 000 3 040 6 000	S250GD + Z275NA Selon la EN 10346
		154182 154183 154184	2 000 3 040 6 000	S235JR, galvanisé à chaud Selon la EN 10025-2
		154404	6 000	V4A (1.4404) Selon la EN 10088-2
	Rail MÜPRO MPR 41/42/2.0 H	150968	6 640	S250GD + Z275NA Selon la EN 10346
		154185	6 640	S235JR, galvanisé à chaud Selon la EN 10025-2

Rails MÜPRO

Description du produit

Forme, dimensions, matériaux et revêtement

Annexe A3

Tableau A4 : Dimensions et matériaux des rails MÜPRO MPR 41/82/2.0 H et MPR 41/82/2.5 H

Illustration (Dimensions en mm et pouces)	Référence	N° de l'élément	Longueur [mm]	Matériaux et revêtements
	Rail MÜPRO MPR 41/82/2.0 H	150969	6 640	S250GD + Z275NA Selon la EN 10346
		154186	6 640	S235JR, galvanisé à chaud Selon la EN 10025-2
		154406	6 000	V4A (1.4404) Selon la EN 10088-2
	Rail MÜPRO MPR 41/82/2.5 H	177352	6 000	S250GD + Z275NA Selon la EN 10346

Les doubles canaux sont constitués de deux profils simples MPR 41/41/2.5, reliés à l'arrière des rails par un assemblage par emboîtement et par liaison mécanique, de type sertissage ou soudage.


Rails MÜPRO

Description du produit

Forme, dimensions, matériaux et revêtement

Annexe A4

Tableau A5 : Dimensions et matériaux des rails MÜPRO MPR 41/124/2.5 H

Illustration (Dimensions en mm et pouces)	Référence	N° de l'élément	Longueur [mm]	Matériaux et revêtements
	Rail MÜPRO MPR 41/124/2.5 H	151050	6 640	S250GD + Z275NA Selon la EN 10346
		154187	6 640	S235JR, galvanisé à chaud Selon la EN 10025-2
		154407	6 000	V4A (1.4404) Selon la EN 10088-2

Les doubles canaux sont constitués de deux profils simples MPR 41/41/2.5, reliés à l'arrière des rails par un assemblage par emboîtement et par liaison mécanique, de type sertissage ou soudage.

Rails MÜPRO

Description du produit

Forme, dimensions, matériaux et revêtement

Annexe A5

Précisions sur le domaine d'emploi

- Les rails MÜPRO sont utilisés pour reprendre les charges des composants de service du bâtiment tel que les conduits et équipement pour les sprinklers, l'eau, le chauffage, le refroidissement, la ventilation, les systèmes électriques et autres à température ambiante et en cas d'incendie. Les rails du Système MT de Hilti remplissent cette fonction de reprise de charges dans les conditions décrites dans la section 2 de la présente Evaluation Technique Européenne.
- Les rails MÜPRO MPR (sans considération de longueur ou de revêtement) faisant partie de cette Evaluation Technique Européenne sont utilisés pour des applications à température ambiante.

Rails MÜPRO

Cross-section characteristics

Annexe B1

Tableau B1 : Propriétés de la section des rails Müpro MPR 41/21/1.5, zone perforée, trou circulaire

Description	Symbol	Value	Unit	Comment
Cross-sectional area	A	131,28	mm ²	
	A _{geom}	131,28	mm ²	geometric cross-sectional area (not ideal)
Shear areas	A _y	39,22	mm ²	
	A _z	42,59	mm ²	
Centroid position	y _{s,0}	20,50	mm	relative to zero point
	z _{s,0}	11,13	mm	
Moments of inertia	I _y	7776,64	mm ⁴	about centroidal axes y
	I _z	35532,19	mm ⁴	
Inclination of principal axes	α	0,00	°	clockwise
Polar moments of inertia	I _p	43308,83	mm ⁴	
	I _{p,M}	104828,94	mm ⁴	about shear center M
Radii of gyration	i _y	7,70	mm	relative to centroid C
	i _z	16,45	mm	
Polar radii of gyration	i _p	18,16	mm	
	i _{p,M}	28,26	mm	about shear center M
Warping radius of gyration	i _{ω,M}	7,01	mm	
Cross-section weight	G	1,03	kg/m	
Cross-section perimeter	U	181,02	mm	incl. inner side of cells
Torsional constant	I _t	87,34	mm ⁴	calculated analytically
Secondary torsional constant	I _{t,s}	26165,15	mm ⁴	
Location of the shear center	y _{M,0}	20,50	mm	relative to zero point
	z _{M,0}	32,78	mm	
	y _M	0,00	mm	relative to centroid C
	z _M	21,65	mm	
Warping constants	I _{ω,s}	2,181E+07	mm ⁶	relative to centroid C
	I _{ω,M}	5,157E+06	mm ⁶	about shear center M
Auxiliary value for warp rotation	r _{ω,M}	0,000		
Section moduli	W _{y,max}	787,95	mm ³	in distance 9.87 mm
	W _{y,min}	-698,67	mm ³	in distance -11.13 mm
	W _{z,max}	1733,28	mm ³	in distance 20.50 mm
	W _{z,min}	-1733,28	mm ³	in distance -20.50 mm
Warping section moduli	W _{ω,M,max}	14435,36	mm ⁴	in node 40
	W _{ω,M,min}	-14449,92	mm ⁴	in node 28
Torsional section modulus	W _t	58,22	mm ³	
Stability parameters	r _u	-2,88	mm	
	r _{M,v}	-46,17	mm	
Reduction factor	λ _M	0,00	1/mm	

Rails MÜPRO

Cross-section characteristics

Annexe B2

Tableau B2 : Propriétés de la section des rails Müpro MPR 41/21/1.5, zone perforée, trou oblong

Description	Symbol	Value	Unit	Comment
Cross-sectional area	A	129,78	mm ²	
	A _{geom}	129,78	mm ²	geometric cross-sectional area (not ideal)
Shear areas	A _y	39,19	mm ²	
	A _z	42,88	mm ²	
Centroid position	y _{S,0}	20,50	mm	relative to zero point
	z _{S,0}	11,03	mm	
Moments of inertia	I _y	7650,17	mm ⁴	about centroidal axes y
	I _z	35473,56	mm ⁴	
Inclination of principal axes	α	0,00	°	clockwise
Polar moments of inertia	I _p	43123,73	mm ⁴	
	I _{p,M}	104651,83	mm ⁴	about shear center M
Radii of gyration	i _y	7,68	mm	relative to centroid C
	i _z	16,53	mm	
Polar radii of gyration	i _p	18,23	mm	
	i _{p,M}	28,40	mm	about shear center M
Warping radius of gyration	i _{ω,M}	7,01	mm	
Cross-section weight	G	1,02	kg/m	
Cross-section perimeter	U	179,02	mm	incl. inner side of cells
Torsional constant	I _t	87,34	mm ⁴	calculated analytically
Secondary torsional constant	I _{t,s}	26174,55	mm ⁴	
Location of the shear center	y _{M,0}	20,50	mm	relative to zero point
	z _{M,0}	32,80	mm	
	y _M	0,00	mm	relative to centroid C
	z _M	21,77	mm	
Warping constants	I _{ω,S}	2,197E+07	mm ⁶	relative to centroid C
	I _{ω,M}	5,148E+06	mm ⁶	about shear center M
Auxiliary value for warp rotation	r _{ω,M}	0,000		
Section moduli	W _{y,max}	766,94	mm ³	in distance 9.97 mm
	W _{y,min}	-693,89	mm ³	in distance -11.03 mm
	W _{z,max}	1730,42	mm ³	in distance 20.50 mm
	W _{z,min}	-1730,42	mm ³	in distance -20.50 mm
Warping section moduli	W _{ω,M,max}	14419,31	mm ⁴	in node 40
	W _{ω,M,min}	-14434,05	mm ⁴	in node 28
Torsional section modulus	W _t	58,22	mm ³	
Stability parameters	r _u	-2,34	mm	
	r _{M,v}	-45,89	mm	
Reduction factor	λ _M	0,00	1/mm	

Rails MÜPRO

Cross-section characteristics

Annexe B3

Tableau B3 : Propriétés de la section des rails Müpro MPR 41/21/1.5, zone non perforée

Description	Symbol	Value	Unit	Comment
Cross-sectional area	A	149,28	mm ²	
	A _{geom}	149,28	mm ²	geometric cross-sectional area (not ideal)
Shear areas	A _y	39,33	mm ²	
	A _z	39,06	mm ²	
Centroid position	Y _{s,0}	20,50	mm	relative to zero point
	Z _{s,0}	12,23	mm	
Moments of inertia	I _y	9096,32	mm ⁴	about centroidal axes y
	I _z	35748,19	mm ⁴	
Inclination of principal axes	α	0,00	°	clockwise
Polar moments of inertia	I _p	44844,51	mm ⁴	
	I _{p,M}	107407,44	mm ⁴	about shear center M
Radii of gyration	i _y	7,81	mm	relative to centroid C
	i _z	15,47	mm	
Polar radii of gyration	i _p	17,33	mm	
	i _{p,M}	26,82	mm	about shear center M
Warping radius of gyration	i _{ω,M}	6,95	mm	
Cross-section weight	G	1,17	kg/m	
Cross-section perimeter	U	202,02	mm	incl. inner side of cells
Torsional constant	I _t	88,40	mm ⁴	calculated analytically
Secondary torsional constant	I _{t,s}	26122,70	mm ⁴	
Location of the shear center	Y _{M,0}	20,50	mm	relative to zero point
	Z _{M,0}	32,70	mm	
	Y _M	0,00	mm	relative to centroid C
	Z _M	20,47	mm	
Warping constants	I _{ω,s}	2,018E+07	mm ⁶	relative to centroid C
	I _{ω,M}	5,191E+06	mm ⁶	about shear center M
Auxiliary value for warp rotation	r _{ω,M}	0,000		
Section moduli	W _{y,max}	1037,33	mm ³	in distance 8.77 mm
	W _{y,min}	-743,71	mm ³	in distance -12.23 mm
	W _{z,max}	1743,81	mm ³	in distance 20.50 mm
	W _{z,min}	-1743,81	mm ³	in distance -20.50 mm
Warping section moduli	W _{ω,M,max}	14494,55	mm ⁴	in node 37
	W _{ω,M,min}	-14507,29	mm ⁴	in node 25
Torsional section modulus	W _t	58,93	mm ³	
Stability parameters	r _u	-8,39	mm	
	r _{M,v}	-49,33	mm	
Reduction factor	λ _M	0,00	1/mm	

Rails MÜPRO

Cross-section characteristics

Annexe B4

Tableau B4 : Propriétés de la section des rails Müpro MPR 41/21/1.5, section moyennée

Description	Symbol	Value	Unit	Comment
Cross-sectional area	A	136,02	mm ²	
	A _{geom}	136,02	mm ²	geometric cross-sectional area (not ideal)
Shear areas	A _y	24,10	mm ²	
	A _z	41,50	mm ²	
Centroid position	y _{s,0}	20,50	mm	relative to zero point
	z _{s,0}	11,45	mm	
Moments of inertia	I _y	8156,93	mm ⁴	about centroidal axes y
	I _z	35561,44	mm ⁴	
Inclination of principal axes	α	0,00	°	clockwise
Polar moments of inertia	I _p	43718,37	mm ⁴	
	I _{p,M}	105541,42	mm ⁴	about shear center M
Radii of gyration	i _y	7,74	mm	relative to centroid C
	i _z	16,17	mm	
Polar radii of gyration	i _p	17,93	mm	
	i _{p,M}	27,86	mm	about shear center M
Warping radius of gyration	i _{ω,M}	6,99	mm	
Cross-section weight	G	1,07	kg/m	
Cross-section perimeter	U	204,06	mm	incl. inner side of cells
Torsional constant	I _t	74,25	mm ⁴	calculated analytically
Secondary torsional constant	I _{t,s}	25909,94	mm ⁴	
Location of the shear center	y _{M,0}	20,50	mm	relative to zero point
	z _{M,0}	32,77	mm	
	y _M	0,00	mm	relative to centroid C
	z _M	21,32	mm	
Warping constants	I _{ω,s}	2,133E+07	mm ⁶	relative to centroid C
	I _{ω,M}	5,162E+06	mm ⁶	about shear center M
Auxiliary value for warp rotation	r _{ω,M}	0,000		
Section moduli	W _{y,max}	854,01	mm ³	in distance 9.55 mm
	W _{y,min}	-712,48	mm ³	in distance -11.45 mm
	W _{z,max}	1734,70	mm ³	in distance 20.50 mm
	W _{z,min}	-1734,70	mm ³	in distance -20.50 mm
Warping section moduli	W _{ω,M,max}	14443,60	mm ⁴	in node 39
	W _{ω,M,min}	-14457,64	mm ⁴	in node 27
Torsional section modulus	W _t	49,50	mm ³	
Stability parameters	r _u	-4,61	mm	
	r _{M,v}	-47,25	mm	
Reduction factor	λ _M	0,00	1/mm	

Rails MÜPRO

Caractéristiques de la section

Annexe B5

Tableau B5 : Propriétés de la section des rails Müpro MPR 41/21/2.0, zone perforée, trou circulaire

Description	Symbol	Value	Unit	Comment
Cross-sectional area	A	160,32	mm ²	
	A _{geom}	160,32	mm ²	geometric cross-sectional area (not ideal)
Shear areas	A _y	51,97	mm ²	
	A _z	57,42	mm ²	
Centroid position	y _{S,0}	20,50	mm	relative to zero point
	z _{S,0}	10,64	mm	
Moments of inertia	I _y	8783,35	mm ⁴	about centroidal axes y
	I _z	44901,68	mm ⁴	
Inclination of principal axes	α	0,00	°	clockwise
Polar moments of inertia	I _p	53685,03	mm ⁴	
	I _{p,M}	128104,27	mm ⁴	about shear center M
Radii of gyration	i _y	7,40	mm	relative to centroid C
	i _z	16,74	mm	
Polar radii of gyration	i _p	18,30	mm	
	i _{p,M}	28,27	mm	about shear center M
Warping radius of gyration	i _{ω,M}	6,76	mm	
Cross-section weight	G	1,26	kg/m	
Cross-section perimeter	U	168,31	mm	incl. inner side of cells
Torsional constant	I _t	196,26	mm ⁴	calculated analytically
Secondary torsional constant	I _{t,s}	32712,83	mm ⁴	
Location of the shear center	y _{M,0}	20,50	mm	relative to zero point
	z _{M,0}	32,19	mm	
	y _M	0,00	mm	relative to centroid C
	z _M	21,54	mm	
Warping constants	I _{ω,S}	2,671E+07	mm ⁶	relative to centroid C
	I _{ω,M}	5,856E+06	mm ⁶	about shear center M
Auxiliary value for warp rotation	Γ _{ω,M}	0,000		
Section moduli	W _{y,max}	848,08	mm ³	in distance 10.36 mm
	W _{y,min}	-825,25	mm ³	in distance -10.64 mm
	W _{z,max}	2190,33	mm ³	in distance 20.50 mm
	W _{z,min}	-2190,33	mm ³	in distance -20.50 mm
Warping section moduli	W _{ω,M,max}	17539,77	mm ⁴	in node 41
	W _{ω,M,min}	-17558,05	mm ⁴	in node 29
Torsional section modulus	W _t	98,13	mm ³	
Stability parameters	r _u	-0,46	mm	
	r _{M,v}	-43,55	mm	
Reduction factor	λ _M	0,00	1/mm	

Rails MÜPRO

Caractéristiques de la section

Annexe B6

Tableau B6: Propriétés de la section des rails Müpro MPR 41/21/2.0, zone perforée, trou oblong

Description	Symbol	Value	Unit	Comment
Cross-sectional area	A	168,32	mm ²	
	A _{geom}	168,32	mm ²	geometric cross-sectional area (not ideal)
Shear areas	A _y	52,22	mm ²	
	A _z	55,94	mm ²	
Centroid position	Y _{S,0}	20,50	mm	relative to zero point
	Z _{S,0}	11,09	mm	
Moments of inertia	I _y	9453,09	mm ⁴	about centroidal axes y
	I _z	45354,35	mm ⁴	
Inclination of principal axes	α	0,00	°	clockwise
Polar moments of inertia	I _p	54807,43	mm ⁴	
	I _{p,M}	128886,01	mm ⁴	about shear center M
Radii of gyration	i _y	7,49	mm	relative to centroid C
	i _z	16,41	mm	
Polar radii of gyration	i _p	18,04	mm	
	i _{p,M}	27,67	mm	about shear center M
Warping radius of gyration	i _{ω,M}	6,78	mm	
Cross-section weight	G	1,32	kg/m	
Cross-section perimeter	U	176,31	mm	incl. inner side of cells
Torsional constant	I _t	196,26	mm ⁴	calculated analytically
Secondary torsional constant	I _{t,s}	32651,89	mm ⁴	
Location of the shear center	Y _{M,0}	20,50	mm	relative to zero point
	Z _{M,0}	32,07	mm	
	Y _M	0,00	mm	relative to centroid C
	Z _M	20,98	mm	
Warping constants	I _{ω,S}	2,590E+07	mm ⁶	relative to centroid C
	I _{ω,M}	5,922E+06	mm ⁶	about shear center M
Auxiliary value for warp rotation	r _{ω,M}	0,000		
Section moduli	W _{y,max}	953,73	mm ³	in distance 9.91 mm
	W _{y,min}	-852,53	mm ³	in distance -11.09 mm
	W _{z,max}	2212,41	mm ³	in distance 20.50 mm
	W _{z,min}	-2212,41	mm ³	in distance -20.50 mm
Warping section moduli	W _{ω,M,max}	17662,60	mm ⁴	in node 39
	W _{ω,M,min}	-17679,88	mm ⁴	in node 27
Torsional section modulus	W _t	98,13	mm ³	
Stability parameters	r _u	-2,75	mm	
	r _{M,v}	-44,71	mm	
Reduction factor	λ _M	0,00	1/mm	

Rails MÜPRO

Caractéristiques de la section

Annexe B7

Tableau B7: Propriétés de la section des rails Müpro MPR 41/21/2.0, zone non perforée

Description	Symbol	Value	Unit	Comment
Cross-sectional area	A	194,32	mm ²	
	A _{geom}	194,32	mm ²	geometric cross-sectional area (not ideal)
Shear areas	A _y	52,40	mm ²	
	A _z	50,80	mm ²	
Centroid position	Y _{S,0}	20,50	mm	relative to zero point
	Z _{S,0}	12,28	mm	
Moments of inertia	I _y	11250,15	mm ⁴	about centroidal axes y
	I _z	45720,51	mm ⁴	
Inclination of principal axes	α	0,00	°	clockwise
Polar moments of inertia	I _p	56970,66	mm ⁴	
	I _{p,M}	132304,96	mm ⁴	about shear center M
Radii of gyration	i _y	7,61	mm	relative to centroid C
	i _z	15,34	mm	
Polar radii of gyration	i _p	17,12	mm	
	i _{p,M}	26,09	mm	about shear center M
Warping radius of gyration	i _{ω,M}	6,72	mm	
Cross-section weight	G	1,53	kg/m	
Cross-section perimeter	U	198,31	mm	incl. inner side of cells
Torsional constant	I _t	199,62	mm ⁴	calculated analytically
Secondary torsional constant	I _{t,s}	32577,93	mm ⁴	
Location of the shear center	Y _{M,0}	20,50	mm	relative to zero point
	Z _{M,0}	31,97	mm	
	Y _M	0,00	mm	relative to centroid C
	Z _M	19,69	mm	
Warping constants	I _{ω,S}	2,371E+07	mm ⁶	relative to centroid C
	I _{ω,M}	5,975E+06	mm ⁶	about shear center M
Auxiliary value for warp rotation	r _{ω,M}	0,000		
Section moduli	W _{y,max}	1290,38	mm ³	in distance 8.70 mm
	W _{y,min}	-916,02	mm ³	in distance -12.30 mm
	W _{z,max}	2230,27	mm ³	in distance 20.50 mm
	W _{z,min}	-2230,27	mm ³	in distance -20.50 mm
Warping section moduli	W _{ω,M,max}	17759,81	mm ⁴	in node 36
	W _{ω,M,min}	-17774,69	mm ⁴	in node 24
Torsional section modulus	W _t	99,81	mm ³	
Stability parameters	r _u	-8,83	mm	
	r _{M,v}	-48,21	mm	
Reduction factor	λ _M	0,00	1/mm	

Rails MÜPRO

Caractéristiques de la section

Annexe B8

Tableau B8: Propriétés de la section des rails Müpro MPR 41/21/2.0, section moyennée

Description	Symbol	Value	Unit	Comment
Cross-sectional area	A	183,10	mm ²	
	A _{geom}	183,10	mm ²	geometric cross-sectional area (not ideal)
Shear areas	A _y	43,86	mm ²	
	A _z	52,46	mm ²	
Centroid position	y _{S,0}	20,50	mm	relative to zero point
	z _{S,0}	11,81	mm	
Moments of inertia	I _y	10532,80	mm ⁴	about centroidal axes y
	I _z	45450,30	mm ⁴	
Inclination of principal axes	α	0,00	°	clockwise
Polar moments of inertia	I _p	55983,10	mm ⁴	
	I _{p,M}	130945,54	mm ⁴	about shear center M
Radii of gyration	i _y	7,58	mm	relative to centroid C
	i _z	15,76	mm	
Polar radii of gyration	i _p	17,49	mm	
	i _{p,M}	26,74	mm	about shear center M
Warping radius of gyration	i _{ω,M}	6,73	mm	
Cross-section weight	G	1,44	kg/m	
Cross-section perimeter	U	199,63	mm	incl. inner side of cells
Torsional constant	I _t	167,92	mm ⁴	calculated analytically
Secondary torsional constant	I _{t,s}	32546,82	mm ⁴	
Location of the shear center	y _{M,0}	20,50	mm	relative to zero point
	z _{M,0}	32,04	mm	
	y _M	0,00	mm	relative to centroid C
	z _M	20,23	mm	
Warping constants	I _{ω,S}	2,456E+07	mm ⁶	relative to centroid C
	I _{ω,M}	5,936E+06	mm ⁶	about shear center M
Auxiliary value for warp rotation	r _{ω,M}	0,000		
Section moduli	W _{y,max}	1145,89	mm ³	in distance 9.19 mm
	W _{y,min}	-891,99	mm ³	in distance -11.81 mm
	W _{z,max}	2217,09	mm ³	in distance 20.50 mm
	W _{z,min}	-2217,09	mm ³	in distance -20.50 mm
Warping section moduli	W _{ω,M,max}	17689,06	mm ⁴	in node 37
	W _{ω,M,min}	-17704,92	mm ⁴	in node 25
Torsional section modulus	W _t	83,96	mm ³	
Stability parameters	r _u	-6,66	mm	
	r _{M,v}	-47,13	mm	
Reduction factor	λ _M	0,00	1/mm	

Rails MÜPRO

Caractéristiques de la section

Annexe B9

Tableau B9: Propriétés de la section des rails Müpro MPR 41/41/2.0, zone perforée, trou circulaire

Description	Symbol	Value	Unit	Comment
Cross-sectional area	A	240,32	mm ²	
	A _{geom}	240,32	mm ²	geometric cross-sectional area (not ideal)
Shear areas	A _y	44,26	mm ²	
	A _z	136,15	mm ²	
Centroid position	y _{s,0}	20,50	mm	relative to zero point
	z _{s,0}	20,39	mm	
Moments of inertia	I _y	49227,59	mm ⁴	about centroidal axes y
	I _z	75348,35	mm ⁴	
Inclination of principal axes	α	0,00	°	clockwise
Polar moments of inertia	I _p	124575,94	mm ⁴	
	I _{p,M}	560274,16	mm ⁴	about shear center M
Radii of gyration	i _y	14,31	mm	relative to centroid C
	i _z	17,71	mm	
Polar radii of gyration	i _p	22,77	mm	
	i _{p,M}	48,28	mm	about shear center M
Warping radius of gyration	i _{ω,M}	7,41	mm	
Cross-section weight	G	1,89	kg/m	
Cross-section perimeter	U	248,31	mm	incl. inner side of cells
Torsional constant	I _t	302,92	mm ⁴	calculated analytically
Secondary torsional constant	I _{t,s}	78591,10	mm ⁴	
Location of the shear center	y _{M,0}	20,50	mm	relative to zero point
	z _{M,0}	62,97	mm	
	y _M	0,00	mm	relative to centroid C
	z _M	42,58	mm	
Warping constants	I _{ω,s}	1,675E+08	mm ⁶	relative to centroid C
	I _{ω,M}	3,078E+07	mm ⁶	about shear center M
Auxiliary value for warp rotation	r _{ω,M}	0,000		
Section moduli	W _{y,max}	2388,89	mm ³	in distance 20.61 mm
	W _{y,min}	-2413,94	mm ³	in distance -20.39 mm
	W _{z,max}	3675,53	mm ³	in distance 20.50 mm
	W _{z,min}	-3675,53	mm ³	in distance -20.50 mm
Warping section moduli	W _{ω,M,max}	41486,76	mm ⁴	in node 43
	W _{ω,M,min}	-41511,21	mm ⁴	in node 31
Torsional section modulus	W _t	151,46	mm ³	
Stability parameters	r _u	0,76	mm	
	r _{M,v}	-84,39	mm	
Reduction factor	λ _M	0,00	1/mm	

Rails MÜPRO

Caractéristiques de la section

Annexe B10

Tableau B10 : Propriétés de la section des rails Müpro MPR 41/41/2.0, zone perforée, trou oblong

Description	Symbol	Value	Unit	Comment
Cross-sectional area	A	248,32	mm ²	
	A _{geom}	248,32	mm ²	geometric cross-sectional area (not ideal)
Shear areas	A _y	44,46	mm ²	
	A _z	135,16	mm ²	
Centroid position	Y _{S,0}	20,50	mm	relative to zero point
	Z _{S,0}	21,03	mm	
Moments of inertia	I _y	52206,58	mm ⁴	about centroidal axes y
	I _z	75801,01	mm ⁴	
Inclination of principal axes	α	0,00	°	clockwise
Polar moments of inertia	I _p	128007,59	mm ⁴	
	I _{p,M}	562100,73	mm ⁴	about shear center M
Radii of gyration	i _y	14,50	mm	relative to centroid C
	i _z	17,47	mm	
Polar radii of gyration	i _p	22,70	mm	
	i _{p,M}	47,58	mm	about shear center M
Warping radius of gyration	i _{ω,M}	7,43	mm	
Cross-section weight	G	1,95	kg/m	
Cross-section perimeter	U	256,31	mm	incl. inner side of cells
Torsional constant	I _t	302,92	mm ⁴	calculated analytically
Secondary torsional constant	I _{t,s}	78504,84	mm ⁴	
Location of the shear center	Y _{M,0}	20,50	mm	relative to zero point
	Z _{M,0}	62,84	mm	
	Y _M	0,00	mm	relative to centroid C
	Z _M	41,81	mm	
Warping constants	I _{ω,s}	1,636E+08	mm ⁶	relative to centroid C
	I _{ω,M}	3,102E+07	mm ⁶	about shear center M
Auxiliary value for warp rotation	r _{ω,M}	0,000		
Section moduli	W _{y,max}	2613,61	mm ³	in distance 19.97 mm
	W _{y,min}	-2483,06	mm ³	in distance -21.03 mm
	W _{z,max}	3697,61	mm ³	in distance 20.50 mm
	W _{z,min}	-3697,61	mm ³	in distance -20.50 mm
Warping section moduli	W _{ω,M,max}	41715,30	mm ⁴	in node 38
	W _{ω,M,min}	-41738,90	mm ⁴	in node 26
Torsional section modulus	W _t	151,46	mm ³	
Stability parameters	r _u	-0,77	mm	
	r _{M,v}	-84,39	mm	
Reduction factor	λ _M	0,00	1/mm	

Rails MÜPRO

Caractéristiques de la section

Annexe B11

Tableau B11 : Propriétés de la section des rails Müpro MPR 41/41/2.0, zone perforée, zone non perforée

Description	Symbol	Value	Unit	Comment
Cross-sectional area	A	274,32	mm ²	
	A _{geom}	274,32	mm ²	geometric cross-sectional area (not ideal)
Shear areas	A _y	44,62	mm ²	
	A _z	129,72	mm ²	
Centroid position	Y _{s,0}	20,50	mm	relative to zero point
	Z _{s,0}	22,82	mm	
Moments of inertia	I _y	60688,80	mm ⁴	about centroidal axes y
	I _z	76167,18	mm ⁴	
Inclination of principal axes	α	0,00	°	clockwise
Polar moments of inertia	I _p	136855,98	mm ⁴	
	I _{p,M}	573636,69	mm ⁴	about shear center M
Radii of gyration	i _y	14,87	mm	relative to centroid C
	i _z	16,66	mm	
Polar radii of gyration	i _p	22,34	mm	
	i _{p,M}	45,73	mm	about shear center M
Warping radius of gyration	i _{ω,M}	7,38	mm	
Cross-section weight	G	2,15	kg/m	
Cross-section perimeter	U	278,31	mm	incl. inner side of cells
Torsional constant	I _t	306,28	mm ⁴	calculated analytically
Secondary torsional constant	I _{t,s}	78421,05	mm ⁴	
Location of the shear center	Y _{M,0}	20,50	mm	relative to zero point
	Z _{M,0}	62,73	mm	
	Y _M	0,00	mm	relative to centroid C
	Z _M	39,90	mm	
Warping constants	I _{ω,s}	1,526E+08	mm ⁶	relative to centroid C
	I _{ω,M}	3,121E+07	mm ⁶	about shear center M
Auxiliary value for warp rotation	r _{ω,M}	0,000		
Section moduli	W _{y,max}	3339,02	mm ³	in distance 18.18 mm
	W _{y,min}	-2658,95	mm ³	in distance -22.82 mm
	W _{z,max}	3715,47	mm ³	in distance 20.50 mm
	W _{z,min}	-3715,47	mm ³	in distance -20.50 mm
Warping section moduli	W _{ω,M,max}	41898,91	mm ⁴	in node 36
	W _{ω,M,min}	-41920,23	mm ⁴	in node 24
Torsional section modulus	W _t	153,14	mm ³	
Stability parameters	r _u	-5,30	mm	
	r _{M,v}	-85,10	mm	
Reduction factor	λ _M	0,00	1/mm	

Rails MÜPRO

Caractéristiques de la section

Annexe B12

Tableau B12 : Propriétés de la section des rails Müpro MPR 41/41/2.0, zone perforée, section moyennée

Description	Symbol	Value	Unit	Comment
Cross-sectional area	A	263,10	mm ²	
	A _{geom}	263,10	mm ²	geometric cross-sectional area (not ideal)
Shear areas	A _y	38,83	mm ²	
	A _z	131,81	mm ²	
Centroid position	Y _{s,0}	20,50	mm	relative to zero point
	Z _{s,0}	22,09	mm	
Moments of inertia	I _y	57229,73	mm ⁴	about centroidal axes y
	I _z	75896,96	mm ⁴	
Inclination of principal axes	α	0,00	°	clockwise
Polar moments of inertia	I _p	133126,69	mm ⁴	
	I _{p,M}	569291,22	mm ⁴	about shear center M
Radii of gyration	i _y	14,75	mm	relative to centroid C
	i _z	16,98	mm	
Polar radii of gyration	i _p	22,49	mm	
	i _{p,M}	46,52	mm	about shear center M
Warping radius of gyration	i _{ω,M}	7,39	mm	
Cross-section weight	G	2,07	kg/m	
Cross-section perimeter	U	279,63	mm	incl. inner side of cells
Torsional constant	I _t	274,58	mm ⁴	calculated analytically
Secondary torsional constant	I _{t,s}	78348,31	mm ⁴	
Location of the shear center	Y _{M,0}	20,50	mm	relative to zero point
	Z _{M,0}	62,81	mm	
	Y _M	0,00	mm	relative to centroid C
	Z _M	40,72	mm	
Warping constants	I _{ω,s}	1,570E+08	mm ⁶	relative to centroid C
	I _{ω,M}	3,107E+07	mm ⁶	about shear center M
Auxiliary value for warp rotation	Γ _{ω,M}	0,000		
Section moduli	W _{y,max}	3026,68	mm ³	in distance 18.91 mm
	W _{y,min}	-2590,57	mm ³	in distance -22.09 mm
	W _{z,max}	3702,29	mm ³	in distance 20.50 mm
	W _{z,min}	-3702,29	mm ³	in distance -20.50 mm
Warping section moduli	W _{ω,M,max}	41764,32	mm ⁴	in node 39
	W _{ω,M,min}	-41786,58	mm ⁴	in node 27
Torsional section modulus	W _t	137,29	mm ³	
Stability parameters	r _u	-3,52	mm	
	r _{M,v}	-84,95	mm	
Reduction factor	λ _M	0,00	1/mm	

Rails MÜPRO

Caractéristiques de la section

Annexe B13

Tableau B13 : Propriétés de la section des rails Müpro MPR 41/41/2.5, zone perforée, trou circulaire

Description	Symbol	Value	Unit	Comment
Cross-sectional area	A	294,51	mm ²	
	A _{geom}	294,51	mm ²	geometric cross-sectional area (not ideal)
Shear areas	A _y	54,98	mm ²	
	A _z	168,69	mm ²	
Centroid position	y _{s,0}	20,50	mm	relative to zero point
	z _{s,0}	20,50	mm	
Moments of inertia	I _y	58672,28	mm ⁴	about centroidal axes y
	I _z	90855,46	mm ⁴	
Inclination of principal axes	α	0,00	°	clockwise
Polar moments of inertia	I _p	149527,74	mm ⁴	
	I _{p,M}	661360,94	mm ⁴	about shear center M
Radii of gyration	i _y	14,11	mm	relative to centroid C
	i _z	17,56	mm	
Polar radii of gyration	i _p	22,53	mm	
	i _{p,M}	47,39	mm	about shear center M
Warping radius of gyration	i _{ω,M}	7,19	mm	
Cross-section weight	G	2,31	kg/m	
Cross-section perimeter	U	245,49	mm	incl. inner side of cells
Torsional constant	I _t	581,57	mm ⁴	calculated analytically
Secondary torsional constant	I _{t,s}	92350,95	mm ⁴	
Location of the shear center	y _{M,0}	20,50	mm	relative to zero point
	z _{M,0}	62,19	mm	
	y _M	0,00	mm	relative to centroid C
	z _M	41,69	mm	
Warping constants	I _{ω,s}	1,923E+08	mm ⁶	relative to centroid C
	I _{ω,M}	3,421E+07	mm ⁶	about shear center M
Auxiliary value for warp rotation	r _{ω,M}	0,000		
Section moduli	W _{y,max}	2861,86	mm ³	in distance 20.50 mm
	W _{y,min}	-2862,27	mm ³	in distance -20.50 mm
	W _{z,max}	4431,97	mm ³	in distance 20.50 mm
	W _{z,min}	-4431,97	mm ³	in distance -20.50 mm
Warping section moduli	W _{ω,M,max}	48581,49	mm ⁴	in node 42
	W _{ω,M,min}	-48608,53	mm ⁴	in node 30
Torsional section modulus	W _t	232,63	mm ³	
Stability parameters	r _u	0,47	mm	
	r _{M,v}	-82,91	mm	
Reduction factor	λ _M	0,00	1/mm	

Rails MÜPRO

Caractéristiques de la section

Annexe B14

Tableau B14 : Propriétés de la section des rails Müpro MPR 41/41/2.5, zone perforée, trou oblong

Description	Symbol	Value	Unit	Comment
Cross-sectional area	A	304,51	mm ²	
	A _{geom}	304,51	mm ²	geometric cross-sectional area (not ideal)
Shear areas	A _y	55,24	mm ²	
	A _z	167,40	mm ²	
Centroid position	Y _{S,0}	20,50	mm	relative to zero point
	Z _{S,0}	21,13	mm	
Moments of inertia	I _y	62261,90	mm ⁴	about centroidal axes y
	I _z	91421,29	mm ⁴	
Inclination of principal axes	α	0,00	°	clockwise
Polar moments of inertia	I _p	153683,20	mm ⁴	
	I _{p,M}	663510,83	mm ⁴	about shear center M
Radii of gyration	i _y	14,30	mm	relative to centroid C
	i _z	17,33	mm	
Polar radii of gyration	i _p	22,47	mm	
	i _{p,M}	46,68	mm	about shear center M
Warping radius of gyration	i _{ω,M}	7,21	mm	
Cross-section weight	G	2,39	kg/m	
Cross-section perimeter	U	253,49	mm	incl. inner side of cells
Torsional constant	I _t	581,57	mm ⁴	calculated analytically
Secondary torsional constant	I _{tS}	92249,79	mm ⁴	
Location of the shear center	Y _{M,0}	20,50	mm	relative to zero point
	Z _{M,0}	62,05	mm	
	Y _M	0,00	mm	relative to centroid C
	Z _M	40,92	mm	
Warping constants	I _{ω,S}	1,877E+08	mm ⁶	relative to centroid C
	I _{ω,M}	3,450E+07	mm ⁶	about shear center M
Auxiliary value for warp rotation	r _{ω,M}	0,000		
Section moduli	W _{y,max}	3133,63	mm ³	in distance 19.87 mm
	W _{y,min}	-2946,46	mm ³	in distance -21.13 mm
	W _{z,max}	4459,58	mm ³	in distance 20.50 mm
	W _{z,min}	-4459,58	mm ³	in distance -20.50 mm
Warping section moduli	W _{ω,M,max}	48867,65	mm ⁴	in node 40
	W _{ω,M,min}	-48893,74	mm ⁴	in node 28
Torsional section modulus	W _t	232,63	mm ³	
Stability parameters	r _u	-1,06	mm	
	r _{M,v}	-82,90	mm	
Reduction factor	λ _M	0,00	1/mm	

Rails MÜPRO

Caractéristiques de la section

Annexe B15

Tableau B15 : Propriétés de la section des rails Müpro MPR 41/41/2.5, zone non perforée

Description	Symbol	Value	Unit	Comment
Cross-sectional area	A	337,01	mm ²	
	A _{geom}	337,01	mm ²	geometric cross-sectional area (not ideal)
Shear areas	A _y	55,45	mm ²	
	A _z	160,43	mm ²	
Centroid position	y _{s,0}	20,50	mm	relative to zero point
	z _{s,0}	22,93	mm	
Moments of inertia	I _y	72458,46	mm ⁴	about centroidal axes y
	I _z	91879,00	mm ⁴	
Inclination of principal axes	α	0,00	°	clockwise
Polar moments of inertia	I _p	164337,46	mm ⁴	
	I _{p,M}	677255,43	mm ⁴	about shear center M
Radii of gyration	i _y	14,66	mm	relative to centroid C
	i _z	16,51	mm	
Polar radii of gyration	i _p	22,08	mm	
	i _{p,M}	44,83	mm	about shear center M
Warping radius of gyration	i _{ω,M}	7,16	mm	
Cross-section weight	G	2,65	kg/m	
Cross-section perimeter	U	274,49	mm	incl. inner side of cells
Torsional constant	I _t	589,77	mm ⁴	calculated analytically
Secondary torsional constant	I _{t,s}	92155,83	mm ⁴	
Location of the shear center	y _{M,0}	20,50	mm	relative to zero point
	z _{M,0}	61,94	mm	
	y _M	0,00	mm	relative to centroid C
	z _M	39,01	mm	
Warping constants	I _{ω,s}	1,747E+08	mm ⁶	relative to centroid C
	I _{ω,M}	3,473E+07	mm ⁶	about shear center M
Auxiliary value for warp rotation	r _{ω,M}	0,000		
Section moduli	W _{y,max}	4009,30	mm ³	in distance 18.07 mm
	W _{y,min}	-3160,35	mm ³	in distance -22.93 mm
	W _{z,max}	4481,90	mm ³	in distance 20.50 mm
	W _{z,min}	-4481,90	mm ³	in distance -20.50 mm
Warping section moduli	W _{ω,M,max}	49097,77	mm ⁴	in node 38
	W _{ω,M,min}	-49121,29	mm ⁴	in node 26
Torsional section modulus	W _t	235,91	mm ³	
Stability parameters	r _u	-5,59	mm	
	r _{M,v}	-83,61	mm	
Reduction factor	λ _M	0,00	1/mm	

Rails MÜPRO

Caractéristiques de la section

Annexe B16

Tableau B16 : Propriétés de la section des rails Müpro MPR 41/41/2.5, section moyennée

Description	Symbol	Value	Unit	Comment
Cross-sectional area	A	322,90	mm ²	
	A _{geom}	322,90	mm ²	geometric cross-sectional area (not ideal)
Shear areas	A _y	48,12	mm ²	
	A _z	163,09	mm ²	
Centroid position	y _{s,0}	20,50	mm	relative to zero point
	z _{s,0}	22,19	mm	
Moments of inertia	I _y	68275,21	mm ⁴	about centroidal axes y
	I _z	91539,19	mm ⁴	
Inclination of principal axes	α	0,00	°	clockwise
Polar moments of inertia	I _p	159814,40	mm ⁴	
	I _{p,M}	672055,17	mm ⁴	about shear center M
Radii of gyration	i _y	14,54	mm	relative to centroid C
	i _z	16,84	mm	
Polar radii of gyration	i _p	22,25	mm	
	i _{p,M}	45,62	mm	about shear center M
Warping radius of gyration	i _{ω,M}	7,17	mm	
Cross-section weight	G	2,53	kg/m	
Cross-section perimeter	U	276,15	mm	incl. inner side of cells
Torsional constant	I _t	527,62	mm ⁴	calculated analytically
Secondary torsional constant	I _{t,s}	92108,61	mm ⁴	
Location of the shear center	y _{M,0}	20,50	mm	relative to zero point
	z _{M,0}	62,02	mm	
	y _M	0,00	mm	relative to centroid C
	z _M	39,83	mm	
Warping constants	I _{ω,s}	1,799E+08	mm ⁶	relative to centroid C
	I _{ω,M}	3,456E+07	mm ⁶	about shear center M
Auxiliary value for warp rotation	r _{ω,M}	0,000		
Section moduli	W _{y,max}	3630,10	mm ³	in distance 18.81 mm
	W _{y,min}	-3076,58	mm ³	in distance -22.19 mm
	W _{z,max}	4465,33	mm ³	in distance 20.50 mm
	W _{z,min}	-4465,33	mm ³	in distance -20.50 mm
Warping section moduli	W _{ω,M,max}	48928,27	mm ⁴	in node 42
	W _{ω,M,min}	-48952,85	mm ⁴	in node 30
Torsional section modulus	W _t	211,05	mm ³	
Stability parameters	r _u	-3,80	mm	
	r _{M,v}	-83,46	mm	
Reduction factor	λ _M	0,00	1/mm	

Rails MÜPRO

Caractéristiques de la section

Annexe B17

Tableau B17 : Propriétés de la section des rails Müpro MPR 41/62/2.5, Zone perforée, trou circulaire

Description	Symbol	Value	Unit	Comment
Cross-sectional area	A	399,51	mm ²	
	A _{geom}	399,51	mm ²	geometric cross-sectional area (not ideal)
Shear areas	A _y	46,25	mm ²	
	A _z	269,34	mm ²	
Centroid position	y _{s,0}	20,50	mm	relative to zero point
	z _{s,0}	30,89	mm	
Moments of inertia	I _y	173330,48	mm ⁴	about centroidal axes y
	I _z	129819,21	mm ⁴	
Inclination of principal axes	α	0,00	°	clockwise
Polar moments of inertia	I _p	303149,70	mm ⁴	
	I _{p,M}	1,894E+06	mm ⁴	about shear center M
Radii of gyration	i _y	20,83	mm	relative to centroid C
	i _z	18,03	mm	
Polar radii of gyration	i _p	27,55	mm	
	i _{p,M}	68,85	mm	about shear center M
Warping radius of gyration	i _{ω,M}	7,10	mm	
Cross-section weight	G	3,14	kg/m	
Cross-section perimeter	U	329,49	mm	incl. inner side of cells
Torsional constant	I _t	800,32	mm ⁴	calculated analytically
Secondary torsional constant	I _{t,s}	143682,79	mm ⁴	
Location of the shear center	y _{M,0}	20,50	mm	relative to zero point
	z _{M,0}	93,99	mm	
	y _M	0,00	mm	relative to centroid C
	z _M	63,10	mm	
Warping constants	I _{ω,s}	6,129E+08	mm ⁶	relative to centroid C
	I _{ω,M}	9,540E+07	mm ⁶	about shear center M
Auxiliary value for warp rotation	r _{ω,M}	0,000		
Section moduli	W _{y,max}	5571,64	mm ³	in distance 31.11 mm
	W _{y,min}	-5611,11	mm ³	in distance -30.89 mm
	W _{z,max}	6332,64	mm ³	in distance 20.50 mm
	W _{z,min}	-6332,64	mm ³	in distance -20.50 mm
Warping section moduli	W _{ω,M,max}	85117,90	mm ⁴	in node 40
	W _{ω,M,min}	-85150,41	mm ⁴	in node 28
Torsional section modulus	W _t	320,13	mm ³	
Stability parameters	r _u	0,67	mm	
	r _{M,v}	-125,52	mm	
Reduction factor	λ _M	0,00	1/mm	

Rails MÜPRO

Caractéristiques de la section

Annexe B18

Tableau B18 : Propriétés de la section des rails Müpro MPR 41/62/2.5, Zone perforée, trou oblong

Description	Symbol	Value	Unit	Comment
Cross-sectional area	A	409,51	mm ²	
	A _{geom}	409,51	mm ²	geometric cross-sectional area (not ideal)
Shear areas	A _y	46,45	mm ²	
	A _z	269,05	mm ²	
Centroid position	y _{s,0}	20,50	mm	relative to zero point
	z _{s,0}	31,62	mm	
Moments of inertia	I _y	182033,75	mm ⁴	about centroidal axes y
	I _z	130385,05	mm ⁴	
Inclination of principal axes	α	0,00	°	clockwise
Polar moments of inertia	I _p	312418,79	mm ⁴	
	I _{p,M}	1,898E+06	mm ⁴	about shear center M
Radii of gyration	i _y	21,08	mm	relative to centroid C
	i _z	17,84	mm	
Polar radii of gyration	i _p	27,62	mm	
	i _{p,M}	68,08	mm	about shear center M
Warping radius of gyration	i _{ω,M}	7,11	mm	
Cross-section weight	G	3,21	kg/m	
Cross-section perimeter	U	337,49	mm	incl. inner side of cells
Torsional constant	I _t	800,32	mm ⁴	calculated analytically
Secondary torsional constant	I _{t,s}	143591,82	mm ⁴	
Location of the shear center	y _{M,0}	20,50	mm	relative to zero point
	z _{M,0}	93,85	mm	
	y _M	0,00	mm	relative to centroid C
	z _M	62,23	mm	
Warping constants	I _{ω,s}	6,015E+08	mm ⁶	relative to centroid C
	I _{ω,M}	9,602E+07	mm ⁶	about shear center M
Auxiliary value for warp rotation	r _{ω,M}	0,000		
Section moduli	W _{y,max}	5991,89	mm ³	in distance 30.38 mm
	W _{y,min}	-5756,92	mm ³	in distance -31.62 mm
	W _{z,max}	6360,25	mm ³	in distance 20.50 mm
	W _{z,min}	-6360,25	mm ³	in distance -20.50 mm
Warping section moduli	W _{ω,M,max}	85541,55	mm ⁴	in node 40
	W _{ω,M,min}	-85573,24	mm ⁴	in node 28
Torsional section modulus	W _t	320,13	mm ³	
Stability parameters	r _u	-0,51	mm	
	r _{M,v}	-124,96	mm	
Reduction factor	λ _M	0,00	1/mm	

Rails MÜPRO

Caractéristiques de la section

Annexe B19

Tableau B19 : Propriétés de la section des rails Müpro MPR 41/62/2.5, zone non perforée

Description	Symbol	Value	Unit	Comment
Cross-sectional area	A	442,01	mm ²	
	A _{geom}	442,01	mm ²	geometric cross-sectional area (not ideal)
Shear areas	A _y	46,61	mm ²	
	A _z	264,05	mm ²	
Centroid position	y _{S,0}	20,50	mm	relative to zero point
	z _{S,0}	33,76	mm	
Moments of inertia	I _y	207600,37	mm ⁴	about centroidal axes y
	I _z	130842,75	mm ⁴	
Inclination of principal axes	α	0,00	°	clockwise
Polar moments of inertia	I _p	338443,12	mm ⁴	
	I _{p,M}	1,928E+06	mm ⁴	about shear center M
Radii of gyration	i _y	21,67	mm	relative to centroid C
	i _z	17,21	mm	
Polar radii of gyration	i _p	27,67	mm	
	i _{p,M}	66,05	mm	about shear center M
Warping radius of gyration	i _{ω,M}	7,08	mm	
Cross-section weight	G	3,47	kg/m	
Cross-section perimeter	U	358,49	mm	incl. inner side of cells
Torsional constant	I _t	808,52	mm ⁴	calculated analytically
Secondary torsional constant	I _{t,s}	143522,71	mm ⁴	
Location of the shear center	y _{M,0}	20,50	mm	relative to zero point
	z _{M,0}	93,73	mm	
	y _M	0,00	mm	relative to centroid C
	z _M	59,97	mm	
Warping constants	I _{ω,S}	5,677E+08	mm ⁶	relative to centroid C
	I _{ω,M}	9,652E+07	mm ⁶	about shear center M
Auxiliary value for warp rotation	r _{ω,M}	0,000		
Section moduli	W _{y,max}	7351,96	mm ³	in distance 28.24 mm
	W _{y,min}	-6148,83	mm ³	in distance -33.76 mm
	W _{z,max}	6382,57	mm ³	in distance 20.50 mm
	W _{z,min}	-6382,57	mm ³	in distance -20.50 mm
Warping section moduli	W _{ω,M,max}	85883,25	mm ⁴	in node 38
	W _{ω,M,min}	-85912,59	mm ⁴	in node 26
Torsional section modulus	W _t	323,41	mm ³	
Stability parameters	r _u	-4,31	mm	
	r _{M,v}	-124,25	mm	
Reduction factor	λ _M	0,00	1/mm	

Rails MÜPRO

Caractéristiques de la section

Annexe B20

Tableau B20 : Propriétés de la section des rails Müpro MPR 41/62/2.5, section moyennée

Description	Symbol	Value	Unit	Comment
Cross-sectional area	A	427,90	mm ²	
	A _{geom}	427,90	mm ²	geometric cross-sectional area (not ideal)
Shear areas	A _y	41,53	mm ²	
	A _z	266,24	mm ²	
Centroid position	Y _{S,0}	20,50	mm	relative to zero point
	Z _{S,0}	32,87	mm	
Moments of inertia	I _y	196969,22	mm ⁴	about centroidal axes y
	I _z	130502,94	mm ⁴	
Inclination of principal axes	α	0,00	°	clockwise
Polar moments of inertia	I _p	327472,16	mm ⁴	
	I _{p,M}	1,917E+06	mm ⁴	about shear center M
Radii of gyration	i _y	21,45	mm	relative to centroid C
	i _z	17,46	mm	
Polar radii of gyration	i _p	27,66	mm	
	i _{p,M}	66,93	mm	about shear center M
Warping radius of gyration	i _{ω,M}	7,08	mm	
Cross-section weight	G	3,36	kg/m	
Cross-section perimeter	U	360,15	mm	incl. inner side of cells
Torsional constant	I _t	746,37	mm ⁴	calculated analytically
Secondary torsional constant	I _{t,s}	143465,26	mm ⁴	
Location of the shear center	Y _{M,0}	20,50	mm	relative to zero point
	Z _{M,0}	93,82	mm	
	Y _M	0,00	mm	relative to centroid C
	Z _M	60,94	mm	
Warping constants	I _{ω,S}	5,815E+08	mm ⁶	relative to centroid C
	I _{ω,M}	9,615E+07	mm ⁶	about shear center M
Auxiliary value for warp rotation	Γ _{ω,M}	0,000		
Section moduli	W _{y,max}	6762,28	mm ³	in distance 29.13 mm
	W _{y,min}	-5991,94	mm ³	in distance -32.87 mm
	W _{z,max}	6366,00	mm ³	in distance 20.50 mm
	W _{z,min}	-6366,00	mm ³	in distance -20.50 mm
Warping section moduli	W _{ω,M,max}	85631,07	mm ⁴	in node 40
	W _{ω,M,min}	-85661,39	mm ⁴	in node 28
Torsional section modulus	W _t	298,55	mm ³	
Stability parameters	r _u	-2,74	mm	
	r _{M,v}	-124,63	mm	
Reduction factor	λ _M	0,00	1/mm	

Rails MÜPRO

Caractéristiques de la section

Annexe B21

Tableau B21 : Propriétés de la section des rails Müpro MPR 41/42/2.0 H, Zone perforée, trou circulaire

Description	Symbol	Value	Unit	Comment
Cross-sectional area	A	320,65	mm ²	
	A _{geom}	320,65	mm ²	geometric cross-sectional area (not ideal)
Shear areas	A _y	103,94	mm ²	
	A _z	122,77	mm ²	
Centroid position	Y _{S,0}	20,50	mm	relative to zero point
	Z _{S,0}	21,00	mm	
Moments of inertia	I _y	51931,06	mm ⁴	about centroidal axes y
	I _z	89803,35	mm ⁴	
Inclination of principal axes	α	0,00	°	clockwise
Polar moments of inertia	I _p	141734,42	mm ⁴	
	I _{p,M}	141734,42	mm ⁴	about shear center M
Radii of gyration	i _y	12,73	mm	relative to centroid C
	i _z	16,74	mm	
Polar radii of gyration	i _p	21,02	mm	
	i _{p,M}	21,02	mm	about shear center M
Warping radius of gyration	i _{ω,M}	13,88	mm	
Cross-section weight	G	2,52	kg/m	
Cross-section perimeter	U	302,62	mm	incl. inner side of cells
Torsional constant	I _t	916,96	mm ⁴	calculated analytically
Secondary torsional constant	I _{t,s}	64783,04	mm ⁴	
Location of the shear center	Y _{M,0}	20,50	mm	relative to zero point
	Z _{M,0}	21,00	mm	
	Y _M	0,00	mm	relative to centroid C
	Z _M	0,00	mm	
Warping constants	I _{ω,S}	2,732E+07	mm ⁶	relative to centroid C
	I _{ω,M}	2,732E+07	mm ⁶	about shear center M
Auxiliary value for warp rotation	Γ _{ω,M}	0,000		
Section moduli	W _{y,max}	2472,91	mm ³	in distance 21.00 mm
	W _{y,min}	-2472,91	mm ³	in distance -21.00 mm
	W _{z,max}	4380,65	mm ³	in distance 20.50 mm
	W _{z,min}	-4380,65	mm ³	in distance -20.50 mm
Warping section moduli	W _{ω,M,max}	54240,20	mm ⁴	in node 63
	W _{ω,M,min}	-54242,93	mm ⁴	in node 51
Torsional section modulus	W _t	272,00	mm ³	
Reduction factor	λ _M	0,00	1/mm	

Rails MÜPRO

Caractéristiques de la section

Annexe B22

Tableau B22 : Propriétés de la section des rails Müpro MPR 41/42/2.0 H, Zone perforée, trou circulaire

Description	Symbol	Value	Unit	Comment
Cross-sectional area	A	336,65	mm ²	
	A _{geom}	336,65	mm ²	geometric cross-sectional area (not ideal)
Shear areas	A _y	104,43	mm ²	
	A _z	122,78	mm ²	
Centroid position	y _{s,0}	20,50	mm	relative to zero point
	z _{s,0}	21,00	mm	
Moments of inertia	I _y	51952,39	mm ⁴	about centroidal axes y
	I _z	90708,69	mm ⁴	
Inclination of principal axes	α	0,00	°	clockwise
Polar moments of inertia	I _p	142661,08	mm ⁴	
	I _{p,M}	142661,08	mm ⁴	about shear center M
Radii of gyration	i _y	12,42	mm	relative to centroid C
	i _z	16,41	mm	
Polar radii of gyration	i _p	20,59	mm	
	i _{p,M}	20,59	mm	about shear center M
Warping radius of gyration	i _{ω,M}	13,84	mm	
Cross-section weight	G	2,64	kg/m	
Cross-section perimeter	U	310,62	mm	incl. inner side of cells
Torsional constant	I _t	916,96	mm ⁴	calculated analytically
Secondary torsional constant	I _{t,s}	64781,66	mm ⁴	
Location of the shear center	y _{M,0}	20,50	mm	relative to zero point
	z _{M,0}	21,00	mm	
	y _M	0,00	mm	relative to centroid C
	z _M	0,00	mm	
Warping constants	I _{ω,s}	2,733E+07	mm ⁶	relative to centroid C
	I _{ω,M}	2,733E+07	mm ⁶	about shear center M
Auxiliary value for warp rotation	r _{ω,M}	0,000		
Section moduli	W _{y,max}	2473,92	mm ³	in distance 21.00 mm
	W _{y,min}	-2473,92	mm ³	in distance -21.00 mm
	W _{z,max}	4424,81	mm ³	in distance 20.50 mm
	W _{z,min}	-4424,81	mm ³	in distance -20.50 mm
Warping section moduli	W _{ω,M,max}	54241,68	mm ⁴	in node 61
	W _{ω,M,min}	-54244,28	mm ⁴	in node 85
Torsional section modulus	W _t	272,00	mm ³	
Stability parameters	r _u	-2,75	mm	
	r _{M,v}	-44,71	mm	
Reduction factor	λ _M	0,00	1/mm	

Rails MÜPRO

Caractéristiques de la section

Annexe B23

Tableau B23 : Propriétés de la section des rails Müpro MPR 41/42/2.0 H, zone non perforée

Description	Symbol	Value	Unit	Comment
Cross-sectional area	A	388,65	mm ²	
	A _{geom}	388,65	mm ²	geometric cross-sectional area (not ideal)
Shear areas	A _y	104,80	mm ²	
	A _z	122,81	mm ²	
Centroid position	Y _{S,0}	20,50	mm	relative to zero point
	Z _{S,0}	21,00	mm	
Moments of inertia	I _y	52021,72	mm ⁴	about centroidal axes y
	I _z	91441,02	mm ⁴	
Inclination of principal axes	α	0,00	°	clockwise
Polar moments of inertia	I _p	143462,74	mm ⁴	
	I _{p,M}	143462,74	mm ⁴	about shear center M
Radii of gyration	i _y	11,57	mm	relative to centroid C
	i _z	15,34	mm	
Polar radii of gyration	i _p	19,21	mm	
	i _{p,M}	19,21	mm	about shear center M
Warping radius of gyration	i _{ω,M}	13,80	mm	
Cross-section weight	G	3,05	kg/m	
Cross-section perimeter	U	328,62	mm	incl. inner side of cells
Torsional constant	I _t	923,68	mm ⁴	calculated analytically
Secondary torsional constant	I _{t,s}	64780,47	mm ⁴	
Location of the shear center	Y _{M,0}	20,50	mm	relative to zero point
	Z _{M,0}	21,00	mm	
	Y _M	0,00	mm	relative to centroid C
	Z _M	0,00	mm	
Warping constants	I _{ω,S}	2,733E+07	mm ⁶	relative to centroid C
	I _{ω,M}	2,733E+07	mm ⁶	about shear center M
Auxiliary value for warp rotation	r _{ω,M}	0,000		
Section moduli	W _{y,max}	2477,23	mm ³	in distance 21.00 mm
	W _{y,min}	-2477,23	mm ³	in distance -21.00 mm
	W _{z,max}	4460,54	mm ³	in distance 20.50 mm
	W _{z,min}	-4460,54	mm ³	in distance -20.50 mm
Warping section moduli	W _{ω,M,max}	54243,00	mm ⁴	in node 57
	W _{ω,M,min}	-54245,25	mm ⁴	in node 81
Torsional section modulus	W _t	272,00	mm ³	
Reduction factor	λ _M	0,00	1/mm	

Rails MÜPRO

Caractéristiques de la section

Annexe B24

Tableau B24 : Propriétés de la section des rails Müpro MPR 41/42/2.0 H, section moyennée

Description	Symbol	Value	Unit	Comment
Cross-sectional area	A	366,21	mm ²	
	A _{geom}	366,21	mm ²	geometric cross-sectional area (not ideal)
Shear areas	A _y	87,71	mm ²	
	A _z	122,76	mm ²	
Centroid position	y _{s,0}	20,50	mm	relative to zero point
	z _{s,0}	21,00	mm	
Moments of inertia	I _y	51983,44	mm ⁴	about centroidal axes y
	I _z	90900,59	mm ⁴	
Inclination of principal axes	α	0,00	°	clockwise
Polar moments of inertia	I _p	142884,03	mm ⁴	
	I _{p,M}	142884,03	mm ⁴	about shear center M
Radii of gyration	i _y	11,91	mm	relative to centroid C
	i _z	15,76	mm	
Polar radii of gyration	i _p	19,75	mm	
	i _{p,M}	19,75	mm	about shear center M
Warping radius of gyration	i _{ω,M}	13,84	mm	
Cross-section weight	G	2,87	kg/m	
Cross-section perimeter	U	365,26	mm	incl. inner side of cells
Torsional constant	I _t	763,33	mm ⁴	calculated analytically
Secondary torsional constant	I _{t,s}	64858,03	mm ⁴	
Location of the shear center	y _{M,0}	20,50	mm	relative to zero point
	z _{M,0}	21,00	mm	
	y _M	0,00	mm	relative to centroid C
	z _M	0,00	mm	
Warping constants	I _{ω,s}	2,738E+07	mm ⁶	relative to centroid C
	I _{ω,M}	2,738E+07	mm ⁶	about shear center M
Auxiliary value for warp rotation	r _{ω,M}	0,000		
Section moduli	W _{y,max}	2475,40	mm ³	in distance 21.00 mm
	W _{y,min}	-2475,40	mm ³	in distance -21.00 mm
	W _{z,max}	4434,18	mm ³	in distance 20.50 mm
	W _{z,min}	-4434,18	mm ³	in distance -20.50 mm
Warping section moduli	W _{ω,M,max}	54313,00	mm ⁴	in node 63
	W _{ω,M,min}	-54315,45	mm ⁴	in node 87
Torsional section modulus	W _t	182,24	mm ³	
Stability parameters	r _u	-6,66	mm	
	r _{M,v}	-47,13	mm	
Reduction factor	λ _M	0,00	1/mm	

Rails MÜPRO

Caractéristiques de la section

Annexe B25

Tableau B25 : Propriétés de la section des rails Müpro MPR 41/82/2.0 H, Zone perforée, trou circulaire

Description	Symbol	Value	Unit	Comment
Cross-sectional area	A	480,65	mm ²	
	A _{geom}	480,65	mm ²	geometric cross-sectional area (not ideal)
Shear areas	A _y	88,51	mm ²	
	A _z	272,10	mm ²	
Centroid position	Y _{S,0}	20,50	mm	relative to zero point
	Z _{S,0}	41,00	mm	
Moments of inertia	I _y	302445,57	mm ⁴	about centroidal axes y
	I _z	150696,69	mm ⁴	
Inclination of principal axes	α	0,00	°	clockwise
Polar moments of inertia	I _p	453142,26	mm ⁴	
	I _{p,M}	453142,26	mm ⁴	about shear center M
Radii of gyration	i _y	25,08	mm	relative to centroid C
	i _z	17,71	mm	
Polar radii of gyration	i _p	30,70	mm	
	i _{p,M}	30,70	mm	about shear center M
Warping radius of gyration	i _{ω,M}	18,04	mm	
Cross-section weight	G	3,77	kg/m	
Cross-section perimeter	U	462,62	mm	incl. inner side of cells
Cross-section outer perimeter	U _o	462,62		
Cross-section inner perimeter	U _i	0,00		
Torsional constant	J	1130,29	mm ⁴	calculated analytically
Torsional constant St. Ven.	J _{St.Ven.}	616,51		
Torsional constant, Bredt portion.	J _{Bredt}	513,78		
Secondary torsional constant	I _{t,s}	136202,24	mm ⁴	
Location of the shear center	Y _{M,0}	20,50	mm	relative to zero point
	Z _{M,0}	41,00	mm	
	Y _M	0,00	mm	relative to centroid C
	Z _M	0,00	mm	
Warping constants	I _{ω,S}	1,474E+08	mm ⁶	relative to centroid C
	I _{ω,M}	1,474E+08	mm ⁶	about shear center M
Auxiliary value for warp rotation	r _{ω,M}	0,000		
Section moduli	W _{y,max}	7376,72	mm ³	in distance 41.00 mm
	W _{y,min}	-7376,72	mm ³	in distance -41.00 mm
	W _{z,max}	7351,06	mm ³	in distance 20.50 mm
	W _{z,min}	-7351,06	mm ³	in distance -20.50 mm
Warping section moduli	W _{ω,M,max}	141870,08	mm ⁴	in node 70
	W _{ω,M,min}	-1,419E+05	mm ⁴	in node 58
Torsional section modulus	W _t	272,00	mm ³	
Reduction factor	λ _M	0,00	1/mm	

Rails MÜPRO

Caractéristiques de la section

Annexe B26

Tableau B26 : Propriétés de la section des rails Müpro MPR 41/82/2.0 H, Zone perforée, trou oblong

Description	Symbol	Value	Unit	Comment
Cross-sectional area	A	496,65	mm ²	
	A _{geom}	496,65	mm ²	geometric cross-sectional area (not ideal)
Shear areas	A _y	88,92	mm ²	
	A _z	272,11	mm ²	
Centroid position	Y _{s,0}	20,50	mm	relative to zero point
	Z _{s,0}	41,00	mm	
Moments of inertia	I _y	302466,90	mm ⁴	about centroidal axes y
	I _z	151602,03	mm ⁴	
Inclination of principal axes	α	0,00	°	clockwise
Polar moments of inertia	I _p	454068,93	mm ⁴	
	I _{p,M}	454068,93	mm ⁴	about shear center M
Radii of gyration	i _y	24,68	mm	relative to centroid C
	i _z	17,47	mm	
Polar radii of gyration	i _p	30,24	mm	
	i _{p,M}	30,24	mm	about shear center M
Warping radius of gyration	i _{ω,M}	18,02	mm	
Cross-section weight	G	3,90	kg/m	
Cross-section perimeter	U	470,62	mm	incl. inner side of cells
Cross-section outer perimeter	U _o	470,62		
Cross-section inner perimeter	U _i	0,00		
Torsional constant	J	1130,29	mm ⁴	calculated analytically
Torsional constant St. Ven.	J _{St.Ven.}	616,51		
Torsional constant, Bredt portion.	J _{Bredt}	513,78		
Secondary torsional constant	I _s	136201,54	mm ⁴	
Location of the shear center	Y _{M,0}	20,50	mm	relative to zero point
	Z _{M,0}	41,00	mm	
	Y _M	0,00	mm	relative to centroid C
	Z _M	0,00	mm	
Warping constants	I _{ω,S}	1,474E+08	mm ⁶	relative to centroid C
	I _{ω,M}	1,474E+08	mm ⁶	about shear center M
Auxiliary value for warp rotation	r _{ω,M}	0,000		
Section moduli	W _{y,max}	7377,24	mm ³	in distance 41.00 mm
	W _{y,min}	-7377,24	mm ³	in distance -41.00 mm
	W _{z,max}	7395,22	mm ³	in distance 20.50 mm
	W _{z,min}	-7395,22	mm ³	in distance -20.50 mm
Warping section moduli	W _{ω,M,max}	141870,81	mm ⁴	in node 60
	W _{ω,M,min}	-1,419E+05	mm ⁴	in node 48
Torsional section modulus	W _t	272,00	mm ³	
Reduction factor	λ _M	0,00	1/mm	

Rails MÜPRO

Caractéristiques de la section

Annexe B27

Tableau B27 : Propriétés de la section des rails Müpro MPR 41/82/2.0 H, zone non perforée

Description	Symbol	Value	Unit	Comment
Cross-sectional area	A	548,65	mm ²	
	A _{geom}	548,65	mm ²	geometric cross-sectional area (not ideal)
Shear areas	A _y	89,24	mm ²	
	A _z	272,12	mm ²	
Centroid position	y _{S,0}	20,50	mm	relative to zero point
	z _{S,0}	41,00	mm	
Moments of inertia	I _y	302536,24	mm ⁴	about centroidal axes y
	I _z	152334,36	mm ⁴	
Inclination of principal axes	α	0,00	°	clockwise
Polar moments of inertia	I _p	454870,59	mm ⁴	
	I _{p,M}	454870,59	mm ⁴	about shear center M
Radii of gyration	i _y	23,48	mm	relative to centroid C
	i _z	16,66	mm	
Polar radii of gyration	i _p	28,79	mm	
	i _{p,M}	28,79	mm	about shear center M
Warping radius of gyration	i _{ω,M}	18,00	mm	
Cross-section weight	G	4,31	kg/m	
Cross-section perimeter	U	488,62	mm	incl. inner side of cells
Cross-section outer perimeter	U _o	488,62		
Cross-section inner perimeter	U _i	0,00		
Torsional constant	J	1137,01	mm ⁴	calculated analytically
Torsional constant St. Ven.	J _{St.Ven.}	623,23		
Torsional constant, Bredt portion.	J _{Bredt}	513,78		
Secondary torsional constant	I _{t,s}	136200,95	mm ⁴	
Location of the shear center	y _{M,0}	20,50	mm	relative to zero point
	z _{M,0}	41,00	mm	
	y _M	0,00	mm	relative to centroid C
	z _M	0,00	mm	
Warping constants	I _{ω,s}	1,474E+08	mm ⁶	relative to centroid C
	I _{ω,M}	1,474E+08	mm ⁶	about shear center M
Auxiliary value for warp rotation	r _{ω,M}	0,000		
Section moduli	W _{y,max}	7378,93	mm ³	in distance 41.00 mm
	W _{y,min}	-7378,93	mm ³	in distance -41.00 mm
	W _{z,max}	7430,94	mm ³	in distance 20.50 mm
	W _{z,min}	-7430,94	mm ³	in distance -20.50 mm
Warping section moduli	W _{ω,M,max}	141871,47	mm ⁴	in node 56
	W _{ω,M,min}	-1,419E+05	mm ⁴	in node 44
Torsional section modulus	W _t	272,00	mm ³	
Reduction factor	λ _M	0,00	1/mm	

Rails MÜPRO

Caractéristiques de la section

Annexe B28

Tableau B28 : Propriétés de la section des rails Müpro MPR 41/82/2.0 H, section moyennée

Description	Symbol	Value	Unit	Comment
Cross-sectional area	A	526,21	mm ²	
	A _{geom}	526,21	mm ²	geometric cross-sectional area (not ideal)
Shear areas	A _y	77,66	mm ²	
	A _z	272,10	mm ²	
Centroid position	Y _{S,0}	20,50	mm	relative to zero point
	Z _{S,0}	41,00	mm	
Moments of inertia	I _y	302498,02	mm ⁴	about centroidal axes y
	I _z	151793,93	mm ⁴	
Inclination of principal axes	α	0,00	°	clockwise
Polar moments of inertia	I _p	454291,95	mm ⁴	
	I _{p,M}	454291,95	mm ⁴	about shear center M
Radii of gyration	i _y	23,98	mm	relative to centroid C
	i _z	16,98	mm	
Polar radii of gyration	i _p	29,38	mm	
	i _{p,M}	29,38	mm	about shear center M
Warping radius of gyration	i _{ω,M}	18,03	mm	
Cross-section weight	G	4,13	kg/m	
Cross-section perimeter	U	525,26	mm	incl. inner side of cells
Cross-section outer perimeter	U _o	489,94		
Cross-section inner perimeter	U _i	35,32		
Torsional constant	J	976,66	mm ⁴	calculated analytically
Torsional constant St. Ven.	J _{St.Ven.}	559,83		
Torsional constant, Bredt portion.	J _{Bredt}	416,83		
Secondary torsional constant	I _{t,s}	136278,41	mm ⁴	
Location of the shear center	Y _{M,0}	20,50	mm	relative to zero point
	Z _{M,0}	41,00	mm	
	Y _M	0,00	mm	relative to centroid C
	Z _M	0,00	mm	
Warping constants	I _{ω,s}	1,476E+08	mm ⁶	relative to centroid C
	I _{ω,M}	1,476E+08	mm ⁶	about shear center M
Auxiliary value for warp rotation	r _{ω,M}	0,000		
Section moduli	W _{y,max}	7378,00	mm ³	in distance 41.00 mm
	W _{y,min}	-7378,00	mm ³	in distance -41.00 mm
	W _{z,max}	7404,58	mm ³	in distance 20.50 mm
	W _{z,min}	-7404,58	mm ³	in distance -20.50 mm
Warping section moduli	W _{ω,M,max}	141969,27	mm ⁴	in node 62
	W _{ω,M,min}	-1,420E+05	mm ⁴	in node 50
Torsional section modulus	W _t	182,24	mm ³	
Reduction factor	λ _M	0,00	1/mm	

Rails MÜPRO

Caractéristiques de la section

Annexe B29

Tableau B29 : Propriétés de la section des rails Müpro MPR 41/82/2.5 H, Zone perforée, trou circulaire

Description	Symbol	Value	Unit	Comment
Cross-sectional area	A	589,03	mm ²	
	A _{geom}	589,03	mm ²	geometric cross-sectional area (not ideal)
Shear areas	A _y	109,97	mm ²	
	A _z	340,00	mm ²	
Centroid position	y _{s,0}	20,50	mm	relative to zero point
	z _{s,0}	41,00	mm	
Moments of inertia	I _y	364791,97	mm ⁴	about centroidal axes y
	I _z	181710,92	mm ⁴	
Inclination of principal axes	α	0,00	°	clockwise
Polar moments of inertia	I _p	546502,89	mm ⁴	
	I _{p,M}	546502,89	mm ⁴	about shear center M
Radii of gyration	i _y	24,89	mm	relative to centroid C
	i _z	17,56	mm	
Polar radii of gyration	i _p	30,46	mm	
	i _{p,M}	30,46	mm	about shear center M
Warping radius of gyration	i _{ω,M}	17,59	mm	
Cross-section weight	G	4,62	kg/m	
Cross-section perimeter	U	456,99	mm	incl. inner side of cells
Cross-section outer perimeter	U _o	456,99		
Cross-section inner perimeter	U _i	0,00		
Torsional constant	J	2178,91	mm ⁴	calculated analytically
Torsional constant St. Ven.	J _{St.Ven.}	1189,18		
Torsional constant, Bredt portion.	J _{Bredt}	989,73		
Secondary torsional constant	I _{t,s}	161880,90	mm ⁴	
Location of the shear center	y _{M,0}	20,50	mm	relative to zero point
	z _{M,0}	41,00	mm	
	y _M	0,00	mm	relative to centroid C
	z _M	0,00	mm	
Warping constants	I _{ω,s}	1,691E+08	mm ⁶	relative to centroid C
	I _{ω,M}	1,691E+08	mm ⁶	about shear center M
Auxiliary value for warp rotation	r _{ω,M}	0,000		
Section moduli	W _{y,max}	8897,36	mm ³	in distance 41.00 mm
	W _{y,min}	-8897,36	mm ³	in distance -41.00 mm
	W _{z,max}	8863,95	mm ³	in distance 20.50 mm
	W _{z,min}	-8863,95	mm ³	in distance -20.50 mm
Warping section moduli	W _{ω,M,max}	168325,35	mm ⁴	in node 78
	W _{ω,M,min}	-1,683E+05	mm ⁴	in node 90
Torsional section modulus	W _t	425,00	mm ³	
Reduction factor	λ _M	0,00	1/mm	

Rails MÜPRO

Caractéristiques de la section

Annexe B30

Tableau B30 : Propriétés de la section des rails Müpro MPR 41/82/2.5 H, Zone perforée, trou oblong

Description	Symbol	Value	Unit	Comment
Cross-sectional area	A	609,03	mm ²	
	A _{geom}	609,03	mm ²	geometric cross-sectional area (not ideal)
Shear areas	A _y	110,49	mm ²	
	A _z	340,01	mm ²	
Centroid position	y _{s,0}	20,50	mm	relative to zero point
	z _{s,0}	41,00	mm	
Moments of inertia	I _y	364833,54	mm ⁴	about centroidal axes y
	I _z	182842,59	mm ⁴	
Inclination of principal axes	α	0,00	°	clockwise
Polar moments of inertia	I _p	547676,13	mm ⁴	
	I _{p,M}	547676,13	mm ⁴	about shear center M
Radii of gyration	i _y	24,48	mm	relative to centroid C
	i _z	17,33	mm	
Polar radii of gyration	i _p	29,99	mm	
	i _{p,M}	29,99	mm	about shear center M
Warping radius of gyration	i _{ω,M}	17,57	mm	
Cross-section weight	G	4,78	kg/m	
Cross-section perimeter	U	464,99	mm	incl. inner side of cells
Cross-section outer perimeter	U _o	464,99		
Cross-section inner perimeter	U _i	0,00		
Torsional constant	J	2178,90	mm ⁴	calculated analytically
Torsional constant St. Ven.	J _{St.Ven.}	1189,17		
Torsional constant, Bredt portion.	J _{Bredt}	989,72		
Secondary torsional constant	I _{t,s}	161879,53	mm ⁴	
Location of the shear center	y _{M,0}	20,50	mm	relative to zero point
	z _{M,0}	41,00	mm	
	y _M	0,00	mm	relative to centroid C
	z _M	0,00	mm	
Warping constants	I _{ω,s}	1,691E+08	mm ⁶	relative to centroid C
	I _{ω,M}	1,691E+08	mm ⁶	about shear center M
Auxiliary value for warp rotation	r _{ω,M}	0,000		
Section moduli	W _{y,max}	8898,38	mm ³	in distance 41.00 mm
	W _{y,min}	-8898,38	mm ³	in distance -41.00 mm
	W _{z,max}	8919,15	mm ³	in distance 20.50 mm
	W _{z,min}	-8919,15	mm ³	in distance -20.50 mm
Warping section moduli	W _{ω,M,max}	168326,70	mm ⁴	in node 76
	W _{ω,M,min}	-1,683E+05	mm ⁴	in node 88
Torsional section modulus	W _t	425,00	mm ³	
Reduction factor	λ _M	0,00	1/mm	

Rails MÜPRO

Caractéristiques de la section

Annexe B31

Tableau B31 : Propriétés de la section des rails Müpro MPR 41/82/2.5 H, zone non perforée

Description	Symbol	Value	Unit	Comment
Cross-sectional area	A	674,03	mm ²	
	A _{geom}	674,03	mm ²	geometric cross-sectional area (not ideal)
Shear areas	A _y	110,90	mm ²	
	A _z	340,03	mm ²	
Centroid position	y _{S,0}	20,50	mm	relative to zero point
	z _{S,0}	41,00	mm	
Moments of inertia	I _y	364968,96	mm ⁴	about centroidal axes y
	I _z	183758,00	mm ⁴	
Inclination of principal axes	α	0,00	°	clockwise
Polar moments of inertia	I _p	548726,97	mm ⁴	
	I _{p,M}	548726,97	mm ⁴	about shear center M
Radii of gyration	i _y	23,27	mm	relative to centroid C
	i _z	16,51	mm	
Polar radii of gyration	i _p	28,53	mm	
	i _{p,M}	28,53	mm	about shear center M
Warping radius of gyration	i _{ω,M}	17,56	mm	
Cross-section weight	G	5,29	kg/m	
Cross-section perimeter	U	480,99	mm	incl. inner side of cells
Cross-section outer perimeter	U _o	480,99		
Cross-section inner perimeter	U _i	0,00		
Torsional constant	J	2195,30	mm ⁴	calculated analytically
Torsional constant St. Ven.	J _{St.Ven.}	1205,58		
Torsional constant, Bredt portion.	J _{Bredt}	989,72		
Secondary torsional constant	I _{t,s}	161878,41	mm ⁴	
Location of the shear center	y _{M,0}	20,50	mm	relative to zero point
	z _{M,0}	41,00	mm	
	y _M	0,00	mm	relative to centroid C
	z _M	0,00	mm	
Warping constants	I _{ω,S}	1,691E+08	mm ⁶	relative to centroid C
	I _{ω,M}	1,691E+08	mm ⁶	about shear center M
Auxiliary value for warp rotation	r _{ω,M}	0,000		
Section moduli	W _{y,max}	8901,68	mm ³	in distance 41.00 mm
	W _{y,min}	-8901,68	mm ³	in distance -41.00 mm
	W _{z,max}	8963,81	mm ³	in distance 20.50 mm
	W _{z,min}	-8963,80	mm ³	in distance -20.50 mm
Warping section moduli	W _{ω,M,max}	168327,91	mm ⁴	in node 68
	W _{ω,M,min}	-1,683E+05	mm ⁴	in node 84
Torsional section modulus	W _t	425,00	mm ³	
Reduction factor	λ _M	0,00	1/mm	

Rails MÜPRO

Caractéristiques de la section

Annexe B32

Tableau B32 : Propriétés de la section des rails Müpro MPR 41/82/2.5 H, section moyennée

Description	Symbol	Value	Unit	Comment
Cross-sectional area	A	645,81	mm ²	
	A _{geom}	645,81	mm ²	geometric cross-sectional area (not ideal)
Shear areas	A _y	96,23	mm ²	
	A _z	339,99	mm ²	
Centroid position	y _{S,0}	20,50	mm	relative to zero point
	z _{S,0}	41,00	mm	
Moments of inertia	I _y	364893,88	mm ⁴	about centroidal axes y
	I _z	183078,37	mm ⁴	
Inclination of principal axes	α	0,00	°	clockwise
Polar moments of inertia	I _p	547972,26	mm ⁴	
	I _{p,M}	547972,26	mm ⁴	about shear center M
Radii of gyration	i _y	23,77	mm	relative to centroid C
	i _z	16,84	mm	
Polar radii of gyration	i _p	29,13	mm	
	i _{p,M}	29,13	mm	about shear center M
Warping radius of gyration	i _{ω,M}	17,58	mm	
Cross-section weight	G	5,07	kg/m	
Cross-section perimeter	U	518,31	mm	incl. inner side of cells
Cross-section outer perimeter	U _o	482,65		
Cross-section inner perimeter	U _i	35,66		
Torsional constant	J	1884,96	mm ⁴	calculated analytically
Torsional constant St. Ven.	J _{St.Ven.}	1081,28		
Torsional constant, Bredt portion.	J _{Bredt}	803,69		
Secondary torsional constant	I _{t,s}	162026,91	mm ⁴	
Location of the shear center	y _{M,0}	20,50	mm	relative to zero point
	z _{M,0}	41,00	mm	
	y _M	0,00	mm	relative to centroid C
	z _M	0,00	mm	
Warping constants	I _{ω,S}	1,694E+08	mm ⁶	relative to centroid C
	I _{ω,M}	1,694E+08	mm ⁶	about shear center M
Auxiliary value for warp rotation	r _{ω,M}	0,000		
Section moduli	W _{y,max}	8899,85	mm ³	in distance 41.00 mm
	W _{y,min}	-8899,85	mm ³	in distance -41.00 mm
	W _{z,max}	8930,65	mm ³	in distance 20.50 mm
	W _{z,min}	-8930,65	mm ³	in distance -20.50 mm
Warping section moduli	W _{ω,M,max}	168513,19	mm ⁴	in node 79
	W _{ω,M,min}	-1,685E+05	mm ⁴	in node 90
Torsional section modulus	W _t	283,90	mm ³	
Reduction factor	λ _M	0,00	1/mm	

Rails MÜPRO

Caractéristiques de la section

Annexe B33

Tableau B33 : Propriétés de la section des rails Müpro MPR 41/124/2.5 H, zone perforée, trou circulaire

Description	Symbol	Value	Unit	Comment
Cross-sectional area	A	799,03	mm ²	
	A _{geom}	799,03	mm ²	geometric cross-sectional area (not ideal)
Shear areas	A _y	92,50	mm ²	
	A _z	528,27	mm ²	
Centroid position	Y _{s,0}	20,50	mm	relative to zero point
	Z _{s,0}	62,00	mm	
Moments of inertia	I _y	1,120E+06	mm ⁴	about centroidal axes y
	I _z	259638,43	mm ⁴	
Inclination of principal axes	α	0,00	°	clockwise
Polar moments of inertia	I _p	1,379E+06	mm ⁴	
	I _{p,M}	1,379E+06	mm ⁴	about shear center M
Radii of gyration	i _y	37,43	mm	relative to centroid C
	i _z	18,03	mm	
Polar radii of gyration	i _p	41,55	mm	
	i _{p,M}	41,55	mm	about shear center M
Warping radius of gyration	i _{ω,M}	18,97	mm	
Cross-section weight	G	6,27	kg/m	
Cross-section perimeter	U	624,99	mm	incl. inner side of cells
Cross-section outer perimeter	U _o	624,99		
Cross-section inner perimeter	U _i	0,00		
Torsional constant	J	2616,40	mm ⁴	calculated analytically
Torsional constant St. Ven.	J _{St.Ven.}	1626,68		
Torsional constant, Bredt portion.	J _{Bredt}	989,72		
Secondary torsional constant	I _{t,s}	241187,79	mm ⁴	
Location of the shear center	Y _{M,0}	20,50	mm	relative to zero point
	Z _{M,0}	62,00	mm	
	Y _M	0,00	mm	relative to centroid C
	Z _M	0,00	mm	
Warping constants	I _{ω,s}	4,962E+08	mm ⁶	relative to centroid C
	I _{ω,M}	4,962E+08	mm ⁶	about shear center M
Auxiliary value for warp rotation	r _{ω,M}	0,000		
Section moduli	W _{y,max}	18059,12	mm ³	in distance 62.00 mm
	W _{y,min}	-18059,12	mm ³	in distance -62.00 mm
	W _{z,max}	12665,29	mm ³	in distance 20.50 mm
	W _{z,min}	-12665,29	mm ³	in distance -20.50 mm
Warping section moduli	W _{ω,M,max}	319229,22	mm ⁴	in node 76
	W _{ω,M,min}	-3,192E+05	mm ⁴	in node 88
Torsional section modulus	W _t	425,00	mm ³	
Reduction factor	λ _M	0,00	1/mm	

Rails MÜPRO

Caractéristiques de la section

Annexe B34

Tableau B34 : Propriétés de la section des rails Müpro MPR 41/124/2.5 H, Zone perforée, trou oblong

Description	Symbol	Value	Unit	Comment
Cross-sectional area	A	819,03	mm ²	
	A _{geom}	819,03	mm ²	geometric cross-sectional area (not ideal)
Shear areas	A _y	92,90	mm ²	
	A _z	528,27	mm ²	
Centroid position	y _{S,0}	20,50	mm	relative to zero point
	z _{S,0}	62,00	mm	
Moments of inertia	I _y	1,120E+06	mm ⁴	about centroidal axes y
	I _z	260770,10	mm ⁴	
Inclination of principal axes	α	0,00	°	clockwise
Polar moments of inertia	I _p	1,380E+06	mm ⁴	
	I _{p,M}	1,380E+06	mm ⁴	about shear center M
Radii of gyration	i _y	36,97	mm	relative to centroid C
	i _z	17,84	mm	
Polar radii of gyration	i _p	41,05	mm	
	i _{p,M}	41,05	mm	about shear center M
Warping radius of gyration	i _{ω,M}	18,96	mm	
Cross-section weight	G	6,43	kg/m	
Cross-section perimeter	U	632,99	mm	incl. inner side of cells
Cross-section outer perimeter	U _o	632,99		
Cross-section inner perimeter	U _i	0,00		
Torsional constant	J	2616,40	mm ⁴	calculated analytically
Torsional constant St. Ven.	J _{St.Ven.}	1626,67		
Torsional constant, Bredt portion.	J _{Bredt}	989,72		
Secondary torsional constant	I _{t,s}	241187,06	mm ⁴	
Location of the shear center	y _{M,0}	20,50	mm	relative to zero point
	z _{M,0}	62,00	mm	
	y _M	0,00	mm	relative to centroid C
	z _M	0,00	mm	
Warping constants	I _{ω,s}	4,962E+08	mm ⁶	relative to centroid C
	I _{ω,M}	4,962E+08	mm ⁶	about shear center M
Auxiliary value for warp rotation	Γ _{ω,M}	0,000		
Section moduli	W _{y,max}	18059,79	mm ³	in distance 62.00 mm
	W _{y,min}	-18059,79	mm ³	in distance -62.00 mm
	W _{z,max}	12720,49	mm ³	in distance 20.50 mm
	W _{z,min}	-12720,49	mm ³	in distance -20.50 mm
Warping section moduli	W _{ω,M,max}	319230,10	mm ⁴	in node 76
	W _{ω,M,min}	-3,192E+05	mm ⁴	in node 88
Torsional section modulus	W _t	425,00	mm ³	
Reduction factor	λ _M	0,00	1/mm	

Rails MÜPRO

Caractéristiques de la section

Annexe B35

Tableau B35 : Propriétés de la section des rails Müpro MPR 41/124/2.5 H, zone non perforée

Description	Symbol	Value	Unit	Comment
Cross-sectional area	A	884,03	mm ²	
	A _{geom}	884,03	mm ²	geometric cross-sectional area (not ideal)
Shear areas	A _y	93,21	mm ²	
	A _z	528,28	mm ²	
Centroid position	y _{s,0}	20,50	mm	relative to zero point
	z _{s,0}	62,00	mm	
Moments of inertia	I _y	1,120E+06	mm ⁴	about centroidal axes y
	I _z	261685,51	mm ⁴	
Inclination of principal axes	α	0,00	°	clockwise
Polar moments of inertia	I _p	1,382E+06	mm ⁴	
	I _{p,M}	1,382E+06	mm ⁴	about shear center M
Radii of gyration	i _y	35,59	mm	relative to centroid C
	i _z	17,21	mm	
Polar radii of gyration	i _p	39,53	mm	
	i _{p,M}	39,53	mm	about shear center M
Warping radius of gyration	i _{ω,M}	18,95	mm	
Cross-section weight	G	6,94	kg/m	
Cross-section perimeter	U	648,99	mm	incl. inner side of cells
Cross-section outer perimeter	U _o	648,99		
Cross-section inner perimeter	U _i	0,00		
Torsional constant	J	2632,80	mm ⁴	calculated analytically
Torsional constant St. Ven.	J _{St.Ven.}	1643,08		
Torsional constant, Bredt portion.	J _{Bredt}	989,72		
Secondary torsional constant	I _{t,s}	241186,46	mm ⁴	
Location of the shear center	y _{M,0}	20,50	mm	relative to zero point
	z _{M,0}	62,00	mm	
	y _M	0,00	mm	relative to centroid C
	z _M	0,00	mm	
Warping constants	I _{ω,s}	4,962E+08	mm ⁶	relative to centroid C
	I _{ω,M}	4,962E+08	mm ⁶	about shear center M
Auxiliary value for warp rotation	Γ _{ω,M}	0,000		
Section moduli	W _{y,max}	18061,97	mm ³	in distance 62.00 mm
	W _{y,min}	-18061,97	mm ³	in distance -62.00 mm
	W _{z,max}	12765,15	mm ³	in distance 20.50 mm
	W _{z,min}	-12765,15	mm ³	in distance -20.50 mm
Warping section moduli	W _{ω,M,max}	319230,89	mm ⁴	in node 69
	W _{ω,M,min}	-3,192E+05	mm ⁴	in node 85
Torsional section modulus	W _t	425,00	mm ³	
Reduction factor	λ _M	0,00	1/mm	

Rails MÜPRO

Caractéristiques de la section

Annexe B36

Tableau B36 : Propriétés de la section des rails Müpro MPR 41/124/2.5 H, section moyennée

Description	Symbol	Value	Unit	Comment
Cross-sectional area	A	855,81	mm ²	
	A _{geom}	855,81	mm ²	geometric cross-sectional area (not ideal)
Shear areas	A _y	83,06	mm ²	
	A _z	528,26	mm ²	
Centroid position	Y _{S,0}	20,50	mm	relative to zero point
	Z _{S,0}	62,00	mm	
Moments of inertia	I _y	1,120E+06	mm ⁴	about centroidal axes y
	I _z	261005,88	mm ⁴	
Inclination of principal axes	α	0,00	°	clockwise
Polar moments of inertia	I _p	1,381E+06	mm ⁴	
	I _{p,M}	1,381E+06	mm ⁴	about shear center M
Radii of gyration	i _y	36,17	mm	relative to centroid C
	i _z	17,46	mm	
Polar radii of gyration	i _p	40,17	mm	
	i _{p,M}	40,17	mm	about shear center M
Warping radius of gyration	i _{ω,M}	18,97	mm	
Cross-section weight	G	6,72	kg/m	
Cross-section perimeter	U	686,31	mm	incl. inner side of cells
Cross-section outer perimeter	U _o	650,65		
Cross-section inner perimeter	U _i	35,66		
Torsional constant	J	2322,46	mm ⁴	calculated analytically
Torsional constant St. Ven.	J _{St.Ven.}	1518,78		
Torsional constant, Bredt portion.	J _{Bredt}	803,69		
Secondary torsional constant	I _{t,s}	241335,40	mm ⁴	
Location of the shear center	Y _{M,0}	20,50	mm	relative to zero point
	Z _{M,0}	62,00	mm	
	Y _M	0,00	mm	relative to centroid C
	Z _M	0,00	mm	
Warping constants	I _{ω,S}	4,968E+08	mm ⁶	relative to centroid C
	I _{ω,M}	4,968E+08	mm ⁶	about shear center M
Auxiliary value for warp rotation	r _{ω,M}	0,000		
Section moduli	W _{y,max}	18060,76	mm ³	in distance 62.00 mm
	W _{y,min}	-18060,76	mm ³	in distance -62.00 mm
	W _{z,max}	12731,99	mm ³	in distance 20.50 mm
	W _{z,min}	-12731,99	mm ³	in distance -20.50 mm
Warping section moduli	W _{ω,M,max}	319477,47	mm ⁴	in node 76
	W _{ω,M,min}	-3,195E+05	mm ⁴	in node 88
Torsional section modulus	W _t	283,90	mm ³	
Reduction factor	λ _M	0,00	1/mm	

Rails MÜPRO

Caractéristiques de la section

Annexe B37