

### PU-Foams

can à 750 ml

#### Field of application

- For filling of cable bushings, hollow spaces in walls, floors or ceilings, for assembling of joinery as well as for sealing of joints / fugues

#### Advantages

- Environmentally friendly, single-component foam, moisture-curing, CFC-free
- Good adhesion and adhesive strength to all building materials
- Easy to work and quickly hardening
- Low water absorption due to largely closed-cell foam
- Very good thermal insulation
- Fire classification B2 acc. to DIN 4102
- When used with a cartridge gun, the PU-Foam can still be used without any problem after the cartridge has been opened (use PU-Cleaner to clean the nozzle)



#### Features

Temperature range	permanent: -40 °C to +100 °C short-term: -40 °C to +130 °C
Thermal conductivity	0.04 W/mK
Water absorption	0.03 Vol.%
Fire classification (according to DIN 4102)	B2
Application	not sticky after 10 min can be cut after 40 min
Working temperature	+5 °C to +35 °C
Cleaning	remove fresh foam with PU-Cleaner

Type	Contents [ml]	Expanded volume [cm³]	Part no.	Sales unit	Pack unit
PU-Foam	750	approx. 40	140143	12	pieces
PU-Foam for cartridge gun			140141		

### PU-Cleaner

can à 500 ml

#### Field of application

- For the removal of fresh spatters of PU-Foam
- For the cleaning of not-yet-hardened PU-Foam from tools

#### Advantages

- Also suitable for the removal of wax, grease, oil and paint splatterings
- With a combi-adaptor for cleaning the PU cartridge gun



Contents [ml]	Part no.	Sales unit	Pack unit
500	140262	12	pieces

