

MPC-Hammer head bolts

Field of application

- For time-saving, efficient attachment to MPC-Support channels

- For direct insertion in the channel slot – even between the mounting bolts

Advantages

- Ideal for attachment of channel constructions and connecting elements
- Suitable for profiles 38/24, 38/40, 39/52, 40/60, 40/80, 38/48, 38/80 and 40/120



Features



For support channels	Connecting thread	Max. allowable bearing point load capacity of channel [N]	Max. recommended tensile load Fz [N]	Max. recommended transverse load Fq (displacement) [N]	At a tightening torque of [Nm]
38/24	M8	2,200	2,200	600	20
	M10			800	30
38/40, 38/80	M8	5,000	5,000	1,000	20
	M10			1,500	30
39/52	M8	6,700	6,700	1,000	20
	M10			1,500	30
40/60, 40/80, 40/120	M8	8,300	8,300	1,000	20
	M10			1,500	30

Connecting thread	Usable thread length [mm]	Length [mm]	Material	Part no.	Sales unit	Pack unit
M8	20	30	V2A	115331	50	pieces
M10	19			115307		

MPC-Protection caps

for MPC-Support channels and wall hanger brackets

For support channels	Part no.	Sales unit	Pack unit
27/18	106000	100	pieces
28/30	106002		
38/40, 38/80	106006	50	
40/60, 40/120	106008	25	



Washers

for attachment of MPC-Support channels

For thread	Outer diameter [mm]	Thickness [mm]	Part no.		Sales unit	Pack unit
			V2A	V4A		
M8	24	2.0	127190	127199	100	pieces
	30		127204	127207		
M10	35	2.5	127097	127103		
			127106	127112		
M12	37	3.0	127160	127163		

