

MPC-Hammer head fasteners

Field of application

- For time-saving, efficient attachment of pipe clamps to MPC-Support channels

Advantages



- Practical range of lengths
- For insertion at any point into the slot of channel profiles 27/18 and 28/30
- Lateral adjustment at any time, allows perfect alignment of the pipeline after installation
- Various lengths and thread diameters can be combined within the same channel



Features



For support channels	Connecting thread	Length [mm]	Thread length [mm]	Part no.		Sales unit	Pack unit
				V2A	V4A		
27/18, 28/30	M8	25	7	115134	115139	50	pieces
		30	15	115143	115148		
		40	25	115157	115160		
		50	35	115169	115172		
		80	65	115184	115187		
38/40, 40/60	M8	25	7	115050	115059		
		35	20	115053	115077		
		50	35	115098	115095		
	M10	35	18	114978	114993		
	M12	15	115008	115017			



For support channels	Max. allowable bearing point load capacity of channel [N]	MPC-Hammer head fasteners				
		Connecting thread	Max. recommended tensile load Fz [N]	Max. recommended transverse load F0 (displacement) [N]	At a tightening torque of [Nm]	
27/18	1,700	M8	1,000	400	10	
28/30	2,500		M10	2,500	1,000	20
38/40	5,000	M12		2,800	1,200	30
		M12		5,000	1,800	40
40/60	8,300	M8	3,500	1,000	20	
		M10	4,000	1,200	30	
		M12	8,300	1,800	40	