

## **MPC-Quick fasteners**

with external thread, galvanised

## Field of application

■ Secure and easy installation in slot of MPC-Support channel in order to connect pipe clamps

## **Advantages**


- Time-saving attachment in the channel slot, even if subsequently fitted between existing pipe sections
- Simple and secure handling: insert in the MPC-Support channels, turn and the MPC-Quick fastener is fixed. No slipping, no falling out
- Adjustment marks on the side facilitate its positioning in the support channel
- Reduction of installation effort due to integral threaded pin in various lengths
- Threaded pins are secured against unscrewing
- Subsequent height adjustment of the threaded pin facilitates corrections of the installation
- Suitable for all MPC-Support channels 27/18 to 40/120



For profiles 27/18 and 28/30



For profiles 38/24 to 40/120



Features						fire protection certified 38:40-40/120, ≥ M10
For support channels	Connecting thread	Usable thread length L [mm]	Total length [mm]	Part no.	Sales unit	Pack unit
27/18, 28/30	M8	7	30	120890	100	pieces
		25	50	120870		
		45	70	120882		
		65	90	120886		
	M10	30	55	120838		
38/24–40/120	M8	7	35	120894	50	
		30	60	120874		
		40	70	120878		
	M10	7	35	120846		
		25	55	120834		
		50	80	120842		