

## Girder clamps

type TKM Kroko, galvanised

## Field of application

- To be used for static hanging pipe-work, lighting and ventilation shafts, plus many other uses

## Advantages

- Quick and safe setting and removal
- Slip-proof
- Girder clamp TKM bites securely into beam when installed

- No need for screws to set clamp
- Possible to insert threaded rod before setting
- Approved by VdS and FM for the attachment of sprinkler lines



## Features



Size	Max. permitted load [N]
M8	2,000
M10	3,500
M12	5,000

Type	Size	Clamping range [mm]	Hole diameter [mm]	VdS approved*	FM approved*	Part no.	Sales unit	Pack unit
TKM1	M8	8-20	9	●		162302	25	pieces
TKM2	M10		11	●	●	162303		
TKM3	M12		13	●	●	162304		



For installation, observe assembly instructions included with the product.

Strength class 4.6 threaded rods must be used for installation.

For steel profiles with sloping flange surfaces with an inclination of up to 14 %.

When fastening pipes bigger than DN 65, a safety steel strip must be used according to VdS certification.

\* VdS and FM approved by SMK Meister GmbH & Co. KG.

	Part no.	Sales unit	Pack unit
<b>Safety steel strip</b> , galvanised Length 350 mm, material 25 x 3.0 mm	123485	25	pieces