

Single bossed clamps without lining, VdS/FM approval, galvanised

Field of application

- For attachment of sprinkler lines according to VdS/FM guide lines
- For indoor use

Advantages

- Suitable for the attachment of sprinkler lines
- Approved by VdS and FM
- Easy and time-saving assembly of sprinkler pipes
- Tightening bolts with combination cross-head convenient for power driver


- Tightening bolts secured with captive washers
- Flexible connection thread depending on the application



Features



Size	Max. recommended load [N]
3/8"-70 mm	1.900
2 1/2"-6"	4.400
223 mm	5.300



Connecting thread	Size		Clamping range [mm]	Part no.	Sales unit	Pack unit	VdS	FM	Regulatory compliance						
	[inch]	[mm]							VdS Connecting thread	FM Connecting thread	B	b	H1	H	V
M8/M10	3/8		14–18	173451	100	pieces	•		M8/M10	-	50	20	39	27,5	M6 x 25
	1/2		19–25	173452			•				57		45	30,5	
	3/4		26–30	173453			•	•			64		60	40,5	
	1		31–37	173454			•	•		71	66		43,5		
		40	38–42	173455			•	•		75	70		45,5		
	1 1/4		43–47	173456			•	•		81	76		48,5		
	1 1/2		47–52	173457			•	•		87	78		51,0		
		57	53–57	173458			•	•		91	86		53,5		
		2	58–63	173459			•	•		100	94		57,5		
M10/M12		70	64–71	173474	50		•	•	M10/M12	M10/M12	105	25	99	60,0	M8 x 40
	2 1/2		72–78	173475			•	•			120		108	64,5	
		83	79–85	173476			•	•			126		114	67,5	
	3		85–90	173477			•	•			131		119	70,0	
		98	94–99	173478			•	•			142		129	75,0	
		102	99–104	173479			•	•			146		133	77,0	
	4		108–115	173480			•	•			157		144	82,5	
		122	118–123	173481			•				M12		-	166	
		125	125–130	173482			•		172	159		90,0			
	5		133–140	173483			•		182	169		95,0			
		147	142–148	173484			•		191	178		99,5			
		152	148–153	173485			•		196	183		102,0			
		160	154–160	173486			•		202	189		105,0			
	6		160–169	173487			•		210	197		109,0			
		223	218–226	173493			•		M16			284		40	260
	M12/M16/1/2"														

- ⚠ Single bossed clamps with FM approval 3/4" - 4" are to be used only with connecting thread ≥ M10.
 Single bossed clamps with VdS approval 3/8" - 2" are to be used only with connecting thread ≥ M8.
 Single bossed clamps with VdS approval 70 mm - 4" are to be used only with connecting thread ≥ M10.
 Single bossed clamps with VdS approval 122 mm - 6" are to be used only with connecting thread M12.
 Single bossed clamps with VdS approval 223 mm are to be used only with connecting thread M16.