

### Pipe connectors DUPLO

#### Field of application

- For connecting cast iron (SML) pipes and fittings according to DIN 19522/EN 877

#### Advantages

- Pipe connector with two screws
- Compact design enables fitting in confined spaces
- Wide tightening strap guarantees extensive distribution of the clamping force

- Creased, dimensionally stable transition lip ensures uniform contact of the sealing collar on the pipe, even in the sealing region
- Simple fitting due to combihead bolt with hexagonal longitudinal slot
- Uniform clamping force distribution due to stable seal with large area pressure-plate
- Tightening bolts integrated into the pressure plate, no loose nuts
- Tested and approved by the Material Testing Institute of North Rhine-Westphalia, supervision contract Nr. 117430



Type DN 50–DN 150, one-piece



Type DN 200–DN 300, two-piece



V2A type DN 400, two-piece

#### Features



Material	Type	Nominal SML pipe size [DN]	Pipe outside diameter [mm]	Fastener thread	Hexagonal socket spanner width [SW]	Part no.	Sales unit	Pack unit
Galvanised	one-piece	50	58	M8	10	115214	50	pieces
		70	78			115217		
		80	83			130659		
		100	110			115176		
		125	135			115182		
		150	160			115188		
	two-piece	200	210			115194	25	
		250	274			115200	10	
		300	326			115205	5	
		400	429			115211	4	
V2A			M10	17		1		