

### Pipe connectors MONO

#### Field of application

- For connecting cast iron (SML) pipes and fittings according to DIN 19522/EN 877

#### Advantages

- Simple visual check at the control slot\* if required tightening torque has been reached
- No torque spanner necessary
- The optimum tightening torque can be achieved despite variations in pipe size (within the tolerance)
- The single-bolt pipe connector is easy to fit and easy to handle
- The tightening bolt with hexagonal socket head enables fast fitting to and removal from the pipe
- Tightening strap made of high quality chrome steel

- Uniform tightening due to the wide central fastening
- A double seam at the sealing collar guarantees a strong radial contact with the pipe and allows the quick pre-assembly of pipes and plain fittings
- The strong fastening has a large adjustment range and thus compensates variations in pipe diameter
- The generously dimensioned inlet sealing lip allows easy insertion of the pipe or fitting
- Sealing collar in high-quality, boiling water resistant elastomeric material
- Tested and approved by the Material Testing Institute of North Rhine-Westphalia, supervision contract Nr. 117430



Before tightening the pipe connector: control slot open



Visual check: After tightening the pipe connector: control slot closed

#### Features



Type	Nominal SML pipe size [DN]	Pipe outside diameter [mm]	Fastener thread	Hexagonal socket spanner width [SW]	Part no.	Sales unit	Pack unit
One-piece	50	58	M8	6	115244	50	pieces
	70	78			115253		
	80	83			115262		
	100	110			115223		
	125	135			115229	25	
	150	160			115235	10	
	200**	210	M10	8	144583	5	

\* The function of the MÜPRO control slot is a registered design.

\*\* Pipe connector DN 200 without control slot.