

Securing clamps galvanised

Field of application

- For longitudinal-locking connection of cast iron (SML) pipes according to DIN 19522/EN 877
- For pipe connections with high requirements, e.g. for use in back-pressure and impact zones or for deflections and diameter steps in downcomers

Advantages

- Assembly time reduced by 50 % with the Securing clamp Express thanks to only 2 tightening screws in combination with suspension joint and one-piece design

- Especially strong flanges for absorbing large forces
- Stable wrap-around of pipe enables optimal securing of the pipe connection cast-iron
- Retro-fitting to pipelines that are already laid can be made at any time
- Tested and approved by the Material Testing Institute of North Rhine-Westphalia up to DN 150, supervision contract Nr. 117430
- One-piece securing clamps patent-nr. DE102012001439A1



Securing clamp Express,
type DN 50–DN 150, one-piece



Securing clamp,
type DN 200–DN 300, three-piece



Securing clamp,
type DN 400, four-piece

Model	Type	Nominal SML pipe size [DN]	Pipe outside diameter [mm]	Fastener thread	Max. internal pressure [bar]	Hexagonal socket spanner width [SW]	Part no.	Sales unit	Pack unit
Express for MONO and DUPLO	one-piece	50	58	M8	10	6	152298	5	pieces
		70	78				152299		
		80	83				152300		
		100	110	M10	5	8	152301		
		125	135	152302					
		150	160	152304					
For DUPLO	three-piece	200	210	M12	3	19	123465	1	
		250	274				123437		
		300	326				123441		
	four-piece	400	429				123445		