


### Cramping sets type F1 AH, hot-dip galvanised

#### Field of application

- For attachment of pipe slide to the supporting steel structure
- Applicable as anchor point and as guidance (expansion point) with lift-off securing
- Hot-dip galvanised version for indoor and outdoor applications
- Applicable for pipe slides with a base plate thickness up to 15 mm

#### Advantages

- Pre-assembled sets consisting of cramping elements and the associated threaded pins and nuts for attachment of the pipe slide to the supporting steel structure



Max. flange thickness [mm]	Support profile width [mm]	Loading			Thread	Max. tightening torque [Nm]	Weight [kg/piece]	Part no.	Sales unit	Pack unit
		$F_x$ [kN]	$F_y$ [kN]	$F_z$ [kN]						
26	75–180	–	±4.0	–5.0	M12	22	1.212	167369	1	set
	180–300						1.422	167372		



Applicable for pipe slides with a base plate thickness of up to 15 mm.

		Cramping set type F1 AH short Part no. 167369		Cramping set type F1 AH long Part no. 167372	
norm	profile type	Abbreviation		Abbreviation	
		min.	max.	min.	max.
1025-3	HE-A	HE-A 100	HE-A 180	HE-A 200	HE-A 650
1025-2	HE-B	HE-B 100	HE-B 180	HE-B 200	HE-B 450
1025-1	I	I 80	I 475	I 500	I 600
1025-5	IPE	IPE 80	IPE 400	IPE 450	IPE 600
1025-4	HE-M	HE-M 100	HE-M 180	HE-M 200	HE-M 220
EN 10055	T	T 80	T 140	–	–