


Cramping sets type F, hot-dip galvanised

Field of application

- For attachment of pipe slide to the supporting steel structure
- Applicable as anchor point and as guidance (expansion point) with lift-off securing
- Hot-dip galvanised version for indoor and outdoor applications
- Applicable for all pipe slides



Advantages

- Pre-assembled sets consisting of cramping elements and the associated threaded pins and nuts for attachment of the pipe slide to the supporting steel structure

| Max. flange thickness [mm] | Support profile width [mm] | Loading | | | Thread | Max. tightening torque [Nm] | Weight [kg/piece] | Part no. | Sales unit | Pack unit |
|----------------------------|----------------------------|---------------------|---------------------|---------------------|--------|-----------------------------|-------------------|----------|------------|-----------|
| | | F _x [kN] | F _y [kN] | F _z [kN] | | | | | | |
| 26 | 75–180 | – | ±4.0 | – | M12 | 22 | 1.212 | 167371 | 1 | set |
| | 180–300 | | | | | | | | | |

| | | Cramping set type F short Part no. 167371 | | Cramping set type F long Part no. 167374 | |
|----------|--------------|--|----------|---|----------|
| norm | profile type | Abbreviation | | Abbreviation | |
| | | min. | max. | min. | max. |
| 1025-3 | HE-A | HE-A 100 | HE-A 180 | HE-A 200 | HE-A 650 |
| 1025-2 | HE-B | HE-B 100 | HE-B 180 | HE-B 200 | HE-B 450 |
| 1025-1 | I | I 80 | I 475 | I 500 | I 600 |
| 1025-5 | IPE | IPE 80 | IPE 400 | IPE 450 | IPE 600 |
| 1025-4 | HE-M | HE-M 100 | HE-M 180 | HE-M 200 | HE-M 220 |
| EN 10055 | T | T 80 | T 140 | – | – |